



Safety and protection installations

Surge protection





Our products for your project Towards the future with OBO

Reliable, safe and of the highest quality: Product features such as installation speed, load capacity, functionality and availability are at the forefront of each of our innovations. Discover the whole range of OBO products – in a new structure, allowing us to deal in a more targeted manner with the needs of you, our customers.

It is our aim to be the first port of call for the best and most innovative connections for electrical and data technology infrastructure. Thus, when looking towards the future, we have asked ourselves what we can do to be the best possible partner you could ever imagine, also in the long term. Against this backdrop, we have optimised our structure once again, sharpened our profile and defined our services more clearly. The result: Three new areas of application, which replace our previous seven product units, in order to provide you with a contemporary and user-orientated visual identity and structure, for both products and communication. This helps you to find exactly the products you are looking for in an even faster and simpler manner.

In this catalogue, we will present to you the variety of the entire product range of the safety and protection installations application area. Here, one thing – above all else – is in the spotlight: Safety. Besides our expert knowledge in this field, we place particular emphasis on innovations in product development and comprehensive quality testing, in order to offer you maximum protection at all times.

Our products for surge and lightning protection provide reliable protection against the impacts of thunderstorms and remote switching operations. These can cause not only significant damage to property, but also endanger human lives. The unique, wide product range in the field of fire protection makes OBO one of the few providers who cover all three protection aims and help you to protect people and property as best as possible in case of fire.

OBO – simply better.

OBO Product Worlds



Safety and protection installations

- Surge protection
- Explosion protection
- Lightning protection
- Earthing
- Equipotential bonding
- Insulation
- Cable bandages – prevention of the spread of fire
- Escape route installations – false ceiling mounting
- Fire protection ducts
- Systems for the maintenance of electrical functionality – cable-specific routing variants
- Systems for the maintenance of electrical functionality – standard support structures and routing systems
- Systems for the maintenance of electrical functionality – FireBox T series junction boxes
- Anchoring

You can find additional products in our new Industrial installations and Building installations catalogues



Industrial installations

Cable support systems and connection and fastening systems for industry and construction project infrastructure

- Cable trays
- Mesh cable trays
- Cable ladders
- Industrial ducts
- Support structures
- Electrical installation pipes
- Wiring ducts
- Power supply units
- Distributors
- Junction boxes
- Concealed and cavity wall installations
- Terminals
- Cable glands
- Installation and fastening clips
- Anchors and fastening systems



Building installations

Cable routing and underfloor systems for administrative and functional buildings including architectural solutions

- Electrical installation ducts and trunking
- Device installation ducts and trunking
- Skirting trunking
- Service poles
- Underfloor applications, in screed
- Underfloor applications, in concrete
- Underfloor applications, on-floor
- Service outlets for underfloor applications
- Floor sockets and floor boxes
- Installation housing and support
- Tabletop sockets
- Sockets, switches, data and multimedia technology

Contents

Surge protection

Page 10



Explosion protection

Page 220



Directories


Page 242





**Welcome world.
Welcome to OBO.**

New solutions to improve functionality and the ease of installation – OBO employees all around the world use their abilities and creativity to make this happen. Because we know that each individual market has its special characteristics and that the requirements for our products change within each market, we have paid particular attention to the compatibility of products in their place of use. We always offer our customers intelligent, well-thought-out solutions. Our brands always keep this promise. The OBO global team wishes to make the work of electrical planners and operatives around the world as easy as possible.



Production location




Subsidiary



Representative office

OBO Support & *contact*



***You have a
problem?
We have the
solution!***

OBO Bettermann is more than the sum of its products. In any situation, we are the reliable partner right by your side. You have a problem? We have the solution!

It doesn't matter in which area of industry our support is needed - from industrial and plant engineering to private, public and administrative buildings, as well as in the areas of mobility and renewable energies - we have all that you need.

OBO can not only provide the entire electro-technical infrastructure with the best possible products. We can also support you with sound expert knowledge and more than 100 years of experience, right from the planning phase through to the realisation of your projects. OBO - solutions you can rely on.

You can contact our Customer Service department on:

+49 2373 89 1700

Monday–Thursday
07.30–17.00

Friday
07.30–15.00

export@obo.de



Service



Training



Handling



Certification

Service – OBO can help

Everywhere and in every project phase:

- Competent hotline
- Product and system information, digitally or printed
- Selection and planning aids on the web, as an app, as a CAD application or in printed form
- 2D and 3D product data for planning
- Field service, branch offices and subsidiaries in 60 countries
- Engineering services for major projects

Training courses from OBO

- Seminars and workshops
- Local consultation and training courses
- Planner days

Handling – OBO delivers reliably

With optimised delivery processes:


- Reliable logistics
- Practical transport systems and packaging
- Loading gear handling and disposal concepts

Certification and guarantee

OBO offers safety. Our products fulfil the most important country-specific regulations:

- Conformity (e.g. IEC, VDE, CE, KEMA, KEUR, UL)
- Certification (e.g. DIN EN, DGNB)
- 5-year guarantee for surge protection products
- Guarantee management

Surge protection



Surge protection

	AC power supplies	12
	MCR technology	94
	Data technology	134
	Transmission and reception units	158
	PV systems	174
	Measuring technology	210
	Accessories	214



On the safe side with OBO

With surge protection in the power-side connection compartment (NAR)



According to the IEC/EN standards
IEC 60364-4-44
IEC 60364-5-53
 surge protection is frequently mandatory.



Only 50 mm wide, optionally with FS contact

Solutions from housing to the highest lightning protection class (FPC I)

Type 1+2 surge protection for mounting on 40 mm busbar system

Visual display without power consumption

Screw fastening secures permanent contact to the busbar




LightningController - MCF25-NAR-TNC

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF25-NAR-TNC	255	3	IP20	1	100.800	5096950

Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems


- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 25 kA (10/350) 3-pole
- Fulfils the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with outside cable infeed.



MCF25-NAR-TNC		Type 1+2
SPD to EN 61643-11		Class I+II
SPD to IEC 61643-11		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μ s)	I_n / L-N	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	8.5 kA
Lightning surge current (10/350)	I_{total}	25 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	60 kA
Combined voltage protection level [L-PEN]	$U_{D/L-PEN}$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120 min}$	442 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²


Connection options



Schutzinstalltionen Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25



LightningController - MCF25-NAR-TNC+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF25-NAR-TNC+FS	255	3	IP20	1	102.000	5096953


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 25 kA (10/350) 3-pole
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Building with outside cable infeed.


MCF25-NAR-TNC+FS		
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class II-II
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	8.5 kA
Lightning surge current (10/350)	I_{total}	25 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	60 kA
Combined voltage protection level [L-PEN]	$U_{p/L-PEN}$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120 min}$	442 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²
FM contacts		Changeover
Switching power AC		250V/ 2A
Switching power DC		250V/ 0,1A
Connection cross-section, FM terminals		0,5 - 1,5 mm ²

Connection options





LightningController - MCF30-NAR-TT




Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 30 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with outside cable infeed.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF30-NAR-TT	255	3+N/PE	IP20	1	107.504	5096961


Connection options



MCF30-NAR-TT		
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	7.5 kA
Lightning surge current (10/350)	I_{total}	30 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	80 kA
Protection level [L-N]	U_p	1.5 kV
Protection level [N-PE]	$U_p / N-PE$	1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$	2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_T / N-PE, 200 \text{ ms}$	1200 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²



LightningController - MCF30-NAR-TT+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF30-NAR-TT+FS	255	3+N/PE	IP20	1	107.600	5096963


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 30 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Building with outside cable infeed.


MCF30-NAR-TT+FS	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 7.5 kA
Lightning surge current (10/350)	I_{total} 30 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_p / N-PE$ 1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_{1/N-PE, 200 \text{ ms}}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm ²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²

Connection options





LightningController - MCF38-NAR-TNC




Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 38 kA (10/350) 3-pole
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF38-NAR-TNC	255	3	IP20	1	100.800	5096971


Connection options



MCF38-NAR-TNC		Type 1+2
SPD to EN 61643-11		Class I+II
SPD to IEC 61643-11		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	12.5 kA
Lightning surge current (10/350)	I_{total}	38 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	60 kA
Combined voltage protection level [L-PEN]	$U_d / L-PEN$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²



LightningController – MCF38-NAR-TNC+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF38-NAR-TNC+FS	255	3	IP20	1	102.000	5096973


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 38 kA (10/350) 3-pole
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Buildings with lightning protection or outside cable infeed.


MCF38-NAR-TNC+FS		
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class II-II
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	12.5 kA
Lightning surge current (10/350)	I_{total}	38 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	60 kA
Combined voltage protection level [L-PEN]	$U_{p/L-PEN}$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120 min}$	442 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²
FM contacts		Changeover
Switching power AC		250V/ 2A
Switching power DC		250V/ 0,1A
Connection cross-section, FM terminals		0,5 - 1,5 mm ²

Connection options





LightningController - MCF50-NAR-TT




Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 50 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF50-NAR-TT	255	3+N/PE	IP20	1	106.700	5096975


Connection options



MCF50-NAR-TT		Type 1+2
SPD to EN 61643-11		Class I+II
SPD to IEC 61643-11		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	12.5 kA
Lightning surge current (10/350)	I_{total}	50 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	80 kA
Protection level [L-N]	U_p	1.5 kV
Protection level [N-PE]	$U_p / N-PE$	1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$	2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_t / N-PE, 200 \text{ ms}$	1200 V
Max. mains-side overcurrent protection		160 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²



LightningController - MCF50-NAR-TT+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF50-NAR-TT+FS	255	3+N/PE	IP20	1	107.500	5096977


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 50 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 160 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Building with lightning protection or outside cable infeed.


MCF50-NAR-TT+FS	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.5 kV
Protection level [N-PE]	$U_p / N-PE$ 1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$ 2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$ 442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_{1/N-PE, 200 \text{ ms}}$ 1200 V
Max. mains-side overcurrent protection	160 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE
Conductor cross-section, flexible (fine-wire)	10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	10 - 35 mm ²
FM contacts	Changeover
Switching power AC	250V/ 2A
Switching power DC	250V/ 0,1A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²

Connection options





LightningController – MCF75-NAR-TNC




Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 75 kA (10/350) 3-pole
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 315 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF75-NAR-TNC	255	3	IP20	1	100.800	5096982


Connection options



MCF75-NAR-TNC		Type 1+2
SPD to EN 61643-11		Class I+II
SPD to IEC 61643-11		Class I+II
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	25 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	25 kA
Lightning surge current (10/350)	I_{total}	75 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	75 kA
Combined voltage protection level [L-PEN]	$U_d / L-PEN$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
Max. mains-side overcurrent protection		315 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²



LightningController - MCF75-NAR-TNC+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF75-NAR-TNC+FS	255	3	IP20	1	102.000	5096983


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-C systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 75 kA (10/350) 3-pole
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 315 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Buildings with lightning protection or outside cable infeed.


MCF75-NAR-TNC+FS		
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class II-II
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	25 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	25 kA
Lightning surge current (10/350)	I_{total}	75 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	75 kA
Combined voltage protection level [L-PEN]	$U_{p/L-PEN}$	1.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_{T/L-N, 120 min}$	442 V
Max. mains-side overcurrent protection		315 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²
FM contacts		Changeover
Switching power AC		250V/ 2A
Switching power DC		250V/ 0,1A
Connection cross-section, FM terminals		0,5 - 1,5 mm ²

Connection options





LightningController - MCF100-NAR-TT




Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 100 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 315 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100

Application: Building with lightning protection or outside cable infeed.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF100-NAR-TT	255	3+N/PE	IP20	1	107.200	5096985


Connection options



MCF100-NAR-TT		Type 1+2
SPD to EN 61643-11		Class I-II
SPD to IEC 61643-11		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	25 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	25 kA
Lightning surge current (10/350)	I_{total}	100 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	100 kA
Protection level [L-N]	U_p	1.5 kV
Protection level [N-PE]	$U_p / N-PE$	1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$	2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_T / N-PE, 200 \text{ ms}$	1200 V
Max. mains-side overcurrent protection		315 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²



LightningController - MCF100-NAR-TT+FS



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF100-NAR-TT+FS	255	3+N/PE	IP20	1	107.600	5096988


Combination arrester, type 1+2, for mounting on 40 mm busbars, for TN-S and TT systems

- Protection level ≤ 1.5 kV to protect the terminals
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 100 kA (10/350) 3+NPE
- Fulfills the requirements of VDE 0100-534 (IEC 60364-5-53)
- Line follow current quenching up to 50 kA and max. backup fuse up to 315 A gL/gG
- Spark gaps for use in the pre-meter area according to VDE-AR-N 4100
- With potential-free changeover contact for remote signalling

Application: Building with lightning protection or outside cable infeed.


MCF100-NAR-TT+FS		Type 1+2
SPD to EN 61643-11		Class I+II
SPD to IEC 61643-11		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	255 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	25 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Lightning surge current (10/350 μ s)	I_{imp}	25 kA
Lightning surge current (10/350)	I_{total}	100 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	100 kA
Protection level [L-N]	U_p	1.5 kV
Protection level [N-PE]	$U_p / N-PE$	1.5 kV
Combined voltage protection level [L-PE]	$U_p / L-PE$	2.5 kV
TOV voltage [L-N] – fail safe mode – 120 min.	$U_T / L-N, 120 \text{ min}$	442 V
TOV voltage [N-PE] – withstand mode – 200 ms	$U_{1/N-PE, 200 \text{ ms}}$	1200 V
Max. mains-side overcurrent protection		315 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE
Conductor cross-section, flexible (fine-wire)		10 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		10 - 35 mm ²
FM contacts		Changeover
Switching power AC		250V/ 2A
Switching power DC		250V/ 0,1A
Connection cross-section, FM terminals		0,5 - 1,5 mm ²

Connection options





LightningController Compact - MCF75




Combination arrester, lightning current and surge arrester, type 1+2

- Protection level ≤ 1.5 kV
- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 75 kA (10/350), 3-pole
- Line following current quenching 50 kA I_{peak}, arrester backup fuse to 315 A gL/gG
- Fulfills the requirements of VDE-AR-N 4100 for use in pre-meter area
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF75-3+FS	255	3	IP20	1	75.000	5096981

Connection options




MCF75-3+FS

SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
SPD to UL 1449		Type 4
Nominal voltage AC (50/60 Hz)	U _n	230 V
Maximum continuous voltage AC	U _c	255 V
Nominal discharge current (8/20 μ s)	I _n / L-N	35 kA
Maximum discharge current (8/20 μ s)	I _{max}	50 kA
Lightning surge current (10/350 μ s)	I _{imp}	25 kA
Lightning surge current (10/350)	I _{total}	75 kA
Arrester surge current (8/20 μ s) [total]	I _{total}	75 kA
Combined voltage protection level [L-PEN]	U _p / L-PEN	1.5 kV
Max. mains-side overcurrent protection		315 A
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T _u	-40 - +80 °C
Protection rating		IP20
Approvals		VDE, UL
Conductor cross-section, flexible (fine-wire)		1.5 - 25 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)		16 - 3 AWG
Conductor cross-section, rigid (single wire/multi-wire)		16 - 2 AWG



LightningController Compact - MCF100



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF100-3+NPE+FS	255	3+N/PE	IP20	1	93.500	5096987


Combination arrester, lightning current and surge arrester, type 1+2

- Protection level ≤ 1.5 kV
- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity up to 100 kA (10/350), 3+NPE
- Line following current quenching 50 kA peak, arrester backup fuse to 315 A gL/gG
- Fulfills the requirements of VDE-AR-N 4100 for use in pre-meter area
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.


MCF100-3+NPE+FS	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 255 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 35 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 25 kA
Lightning surge current (10/350)	I_{total} 100 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 100 kA
Protection level [L-N]	U_p 1.5 kV
Max. mains-side overcurrent protection	315 A
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	VDE, UL
Conductor cross-section, flexible (fine-wire)	1.5 - 25 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 3 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Combination arrester, 1-pole




Combination arrester, type 1+2, for use in TN and TT networks

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 150 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Suitable for use in pre-meter area
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of the highest class I to IV.

Type	Highest continuous voltage V	Version	Pack	Weight	Item no.
			Piece	kg/100 pc.	
MCD 50-B	255	1-pole	1	34.400	5096849


Connection options



MCD 50-B		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	50 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{Total 8/20}$	50 kA
Protection level	U_p	< 1,7 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²



Combination arrester, 1-pole with function display



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B-OS	255	1-pole	1	34.800	5096852

Combination arrester, type 1+2, 1-pole, for use in TN and TT networks:


MCD 50-B-OS: Coordinated lightning current arrester, type 1+2 to EN 61643-11 with visual function display. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or DIN VDE 0185-305.

- Arresting capacity 50 kA (10/350 μs) per pole
- Power consumption < 26 mW/pole
- Protection level < 1.7 kV, allows device protection
- Line follow current quenching 25 kA Ipeak
- Incl. plug caps for labelling the connections
- Encapsulated, non-extinguishing spark gap
- Can be used in standard distributor housings.

Application: Compact surge protection concepts and installations in a distributor.


MCD 50-B-OS			
Nominal voltage	U_N		230 V
Max. continuous operating voltage	U_C		255 V
SPD to EN 61643-11			Type 1+2
SPD to IEC 61643-11			Class I+II
Lightning protection zone LPZ			0-2
Impulse discharge current (10/350)	I_{imp}		50 kA
Lightning surge current (10/350)	I_{total}		50 kA
Nominal discharge current (8/20)	I_n		50 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$		50 kA
Protection level	U_p		< 1,7 kV
Response time	t_A		<100 ns
Follow current quenching capacity Ieff	$I_{fi eff}$		10 kA
Maximum back-up fuse			500 A
Temperature range	ϑ		-40 - +85 °C
Division unit TE (17.5 mm)			2
Protection rating			IP20
Approvals			VDE
Connection cross-section, rigid			10 - 50 mm ²
Connection cross-section, multi-wire			10 - 35 mm ²
Connection cross-section, flexible			10 - 25 mm ²

Connection options





Combination arrester, 1-pole NPE



Combination arrester, type 1+2, N+PE for use in TN-S and TT networks.

MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 to EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.


- Arresting capacity 125 kA (10/350 μ s)
- Conforms to VDE-AR-N 4100
- Incl. plug caps for labelling the connections
- Protection level < 1.5 kV, allows device protection
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.

Highest continuous voltage

Type	V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 125-B NPE	255	NPE	1	46.500	5096865

Connection options




MCD 125-B NPE

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	125 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	125 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	125 kA
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity (eff) [N-PE]	I_{fi}	0.1 kA
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²



Combination arrester, 3-pole



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3	255	3-pole	1	117.000	5096877

Combination arrester, type 1+2, 3-pole, for use in TN-C networks.


Completely pre-terminated and ready for connection, consisting of: 3x MCD 50-B: Type 1+2 (Class B) coordinated lightning current arrester EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 150 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Suitable for use in pre-meter area according to VDE-AR-N 4100
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of the Classes I to IV.


MCD 50-B 3		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	150 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{Total 8/20}$	150 kA
Protection level	U_p	< 1,7 kV
Response time	t_A	<100 ns
Follow current quenching capacity I_{eff}	$I_{fi eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		6
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Connection options





Combination arrester, 3-pole with function display



Combination arrester set, type 1+2, 3-pole, with visual function display, for use in TN-C networks:


Completely pre-terminated and ready for connection, consisting of:
3 x MCD 50-B-OS: Type 1+2 coordinated lightning current arresters to DIN EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 150 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Power consumption < 26 mW/pole
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3-OS	255	3-pole	1	118.000	5096835


Connection options



MCD 50-B 3-OS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	150 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{Total 8/20}$	150 kA
Protection level	U_p	< 1,7 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		6
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Combination arrester, 3-pole + NPE



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3+1	255	3 + NPE	1	168.000	5096879

Combination arrester, type 1+2, 4-pole, for use in TT and TN-S networks.


Completely pre-terminated and ready for connection, consisting of:
 3x MCD 50-B: Coordinated lightning current arrester, type 1+2 to EN 61643-11 and
 1x MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 to EN 61643-11. For interface 0 to 2 (LPZ) in accordance with lightning protection zone concept to IEC 61312-1 and/or VDE 0185-305.

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 125 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Suitable for use in pre-meter area according to VDE-AR-N 4100
- Encapsulated, non-extinguishing spark gaps

Application: Industrial systems and buildings with external lightning protection of the classes I to IV.


MCD 50-B 3+1		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{Total 8/20}$	125 kA
Protection level	U_p	< 1,7 kV
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity I_{eff}	$I_{fi eff}$	10 kA
Follow current quenching capacity (eff) [N-PE]	I_{fi}	0.1 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		8
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Connection options





Combination arrester, 3-pole + NPE with function display



Combination arrester, type 1+2, 4-pole, with visual function display, for use in TN-S and TT networks.


Completely pre-terminated and ready for connection, consisting of:
 3x MCD 50-B-OS: Type 1+2 (Class B) coordinated lightning current arrester EN 61643-11.
 1x MCD 125-B/NPE: Coordinated N-PE spark gap, type 1+2 EN 61643-11 for use in TN-S and TT systems.
 Interface 0 to 1 according to lightning protection zone concept according to IEC 61312-1 and VDE 0185-305.

- Lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity to 50 kA (10/350) per pole and up to 125 kA (10/350) in total
- Protection level < 1.7 kV allows device protection
- Short-circuit resistance 10 kA, arrester backup fuse to 500 A gL/gG
- Power consumption < 26 mW/pole
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of Classes I to IV.

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3+1-OS	255	3+ NPE	1	172.000	5096836

Connection options



MCD 50-B 3+1-OS

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrester surge current (8/20) [total]	$I_{Total 8/20}$	125 kA
Protection level	U_p	< 1,7 kV
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi eff}$	10 kA
Follow current quenching capacity (eff) [N-PE]	I_{fi}	0.1 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		8
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²



Combination arrester MCF Compact

Surge protection energy technology, arrester, type 1+2




- Type 1 + 2 SPD: $I_{imp} = 25$ kA per pole and up to 100 kA in total
- Protection level: < 1.5 kV, usable in coordination with type 3 SPD
- Usable in buildings with lightning protection class 1–4
- Quality according to EN 61643-11 certified by an external testing institute
- Universally usable for industry, offices, commercial and residential buildings
- System protection up to 315 A usable without separate fusing
- Remote signalling, potential-free changeover (RS)
- Variants in three to three-pole+NPE versions
- Operating instructions always available online via QR code
- Space savings of up to 25% (compared to MCD variant)

PA



Combination arrester V50, 1-pole 280 V




Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1-280	280	1	IP20	1	16.400	5093500

Connection options




V50-1-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 1-pole + NPE 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE-280	280	1+N/PE	IP20	1	32.929	5093522


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free change-over contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

V50-1+NPE-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG


Connection options



PA



Combination arrester V50, 1-pole with FS 280 V



Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+FS-280	280	1	IP20	1	16.600	5093502

Connection options




V50-1+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 1-pole + NPE with FS 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-1+NPE+FS-280	280	1+N/PE	IP20	1	30.600	5093531


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.


V50-1+NPE+FS-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_d 1.3 kV
Combined voltage protection level [L-PE]	$U_{d/L-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Combination arrester V50, 2-pole + NPE 280 V




Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free change-over contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-2+NPE-280	280	2+N/PE	IP20	1	44.300	5093524


Connection options



V50-2+NPE-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I-II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_o 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 3-pole 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3-280	280	3	IP20	1	46.500	5093511


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free change-over contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.


V50-3-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{limp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Combination arrester V50, 3-pole with FS 280 V




Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+FS-280	280	3	IP20	1	46.900	5093516


Connection options



V50-3+FS-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 37.5 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_o 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 3-pole + NPE 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+NPE-280	280	3+N/PE	IP20	1	58.800	5093526


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free change-over contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.


V50-3+NPE-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{limp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Combination arrester V50, 3-pole + NPE with FS 280 V




Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-3+NPE+FS-280	280	3+N/PE	IP20	1	59.300	5093533


Connection options



V50-3+NPE+FS-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class II-II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_d 1.3 kV
Combined voltage protection level [L-PE]	$U_{d/L-PE}$ 2.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 4-pole 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-4-280	280	4	IP20	1	61.000	5093513


Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free change-over contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.


V50-4-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{limp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Combination arrester V50, 4-pole with FS 280 V




Lightning current combination arrester, type 1+2

- For lightning current equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current arresting capacity of 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total
- Modular, plug-in arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling (FS) variants have a potential-free changeover contact for remote signalling

Application: Lightning current equipotential bonding for buildings of class III and IV.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-4+FS-280	280	4	IP20	1	61.500	5093518

Connection options



V50-4+FS-280

SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_o 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, KEMA, ÖVE, VDE
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Lightning current and surge arrester MCF 35

Surge protective device for energy technology, arrester, type 1 (industry)




- Lightning current and surge arresters
- High arresting capacity up to 35 kA (10/350) per pin
- Arresters for buildings with lightning protection system
- Visual status display
- With remote signalling
- Simple standard DIN rail mounting
- Labelled connections
- Usable in systems with lightning protection class I-V

The MCF lightning current arresters meet the type 1 requirement class according to IEC 61643-11. These devices protect low-voltage and consumer systems against any type of surges. Several benefits are achieved through the use of the voltage-limiting carbon spark gap. A short response time, a

low protection level and high current leakage capability with long service life. In addition, the devices do not produce any line follow current. If circumstances are uncertain and there is a risk of fire from overloads, the cut-off unit disconnects the arrester safely from the mains.



Lightning arrester MCF 35, 400/690 V, 1-pole with IR




Lightning arrester type 1

- For lightning protection equipotential bonding to DIN EN 62305 (IEC 62305)
- Lightning current arresting capacity 35 kA (10/350) per pole
- Follow current extinguishing 50 kA_{eff}, arrester back-up fuse up to 400 A gL/gG
- Encapsulated, non-extinguishing spark gap arrester for use in distributor housings
- Cut-off unit with visual indicator
- Remote signalling with potential-free changeover contact

Application: Without exception for 400/690 V network systems

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF 35-1+FS-440	440	1-pole	1	98.000	5096974

Connection options




MCF 35-1+FS-440	
Nominal voltage	U_N 400 V
Max. continuous operating voltage	U_C 440 V
SPD to EN 61643-11	Type 1
SPD to IEC 61643-11	Class I
Impulse discharge current (10/350)	I_{imp} 35 kA
Nominal discharge current (8/20)	I_n 35 kA
Protection level	U_p 2,5 kV
Follow current quenching capacity leff	$I_{fi\,eff}$ 50 kA
Maximum back-up fuse	400 A
Protection rating	IP20
Response time	t_A < 100 ns
Temperature range	ϑ -40 - +85 °C



Lightning arrester MCF 35, 400/690 V, 3-pole with IR

AIG

CE EAC 400 V Type 1 LPZ 0→1 5



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF 35-P3+FS-440	440	3-pole	1	400.000	5096976


Lightning arrester type 1

- Fully assembled 3-pole connection unit
 - For lightning protection equipotential bonding according to DIN EN 62305 (IEC 62305)
 - Lightning current arresting capacity 35 kA (10/350) per pole
 - Line following current quenching 50 kA_{eff}, arrester back-up fuse up to 400 A gL/gG
 - Encapsulated, non-extinguishing spark gap arrester for use in distributor housings
 - Cut-off unit with visual indicator
 - Remote signalling with potential-free changeover contact
 - For finished mounting on busbars and walls
- Application: Without exception for 400/690 V power systems

MCF 35-P3+FS-440

Nominal voltage	U_N	400 V
Max. continuous operating voltage	U_C	440 V
SPD to EN 61643-11		Type 1
SPD to IEC 61643-11		Class I
Impulse discharge current (10/350)	I_{imp}	35 kA
Nominal discharge current (8/20)	I_n	35 kA
Protection level	U_p	2,5 kV
Follow current quenching capacity I_{fi}	$I_{fi\ eff}$	50 kA
Maximum back-up fuse		400 A
Protection rating		IP20
Response time	t_A	< 100 ns
Temperature range	ϑ	-40 - +85 °C

Connection options




Surge arrester V20

Surge protection energy technology, type 2 arrester




Schutzinstallationen Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25



- Type 2 SPD: $I_n = 20 \text{ kA (L-N) / 40 \text{ kA (N-PE)}$, up to 60 kA
- Protection level: $< 1.5 \text{ kV}$, usable in coordination with type 3 SPD
- Exceeds the increased requirements according to VDE 0100-443
- Quality according to EN 61643-11 certified by an external testing institute
- Universally usable for industry, offices, commercial and residential buildings
- Locking function with vibration protection
- System protection up to 160 A usable without separate fusing
- Can be installed universally through 90° labelling
- Voltage variants: 75 V, 150 V, 280 V, 320 V, 385 V, 440 V, 550 V
- Optional remote signalling, potential-free changeover contact
- Variants in one to four-pole versions
- Operating instructions always available online via QR code

Surge arrester V20, 1-pole, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1-280	280	1	IP20	1	12.900	5095161

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

V20-1-280


SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 1-pole with remote signaling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+FS-280	280	1	IP20	1	13.100	5095281


Connection options



V20-1+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 40 kA
Protection level [L-N]	U_b 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Surge arrester V20, 1-pole + NPE, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE-280	280	1+N/PE	IP20	1	24.300	5095251

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling


Application: Equipotential bonding in main and sub-distributions.

V20-1+NPE-280


SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 1-pole + NPE and remote signalling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-1+NPE+FS-280	280	1+N/PE	IP20	1	24.600	5095331



Connection options



V20-1+NPE+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_b 1.3 kV
Combined voltage protection level [L-PE]	$U_{D / L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Surge arrester V20, 2-pole, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2-280	280	2	IP20	1	25.600	5095162

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

V20-2-280


SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 2-pole with remote signaling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+FS-280	280	2	IP20	1	25.900	5095282

Connection options




V20-2+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 80 kA
Protection level [L-N]	U_b 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Schutzinstallationen: Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25



Surge arrester V20, 2-pole + NPE, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE-280	280	2+N/PE	IP20	1	34.600	5095252


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.


V20-2+NPE-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 2-pole + NPE and remote signalling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-2+NPE+FS-280	280	2+N/PE	IP20	1	34.800	5095332


Connection options



V20-2+NPE+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_b 1.3 kV
Combined voltage protection level [L-PE]	$U_{D/L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Surge arrester V20, 3-pole, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3-280	280	3	IP20	1	36.000	5095163

Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

V20-3-280


SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 3-pole with remote signaling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+FS-280	280	3	IP20	1	36.400	5095283


Connection options



V20-3+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 120 kA
Protection level [L-N]	U_b 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Surge arrester V20, 3-pole + NPE, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE-280	280	3+N/PE	IP20	1	45.800	5095253


Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.


V20-3+NPE-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Combined voltage protection level [L-PE]	$U_{p/L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 3-pole + NPE and remote signalling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-3+NPE+FS-280	280	3+N/PE	IP20	1	46.300	5095333

Connection options




V20-3+NPE+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_b 1.3 kV
Combined voltage protection level [L-PE]	$U_{D/L-PE}$ 1.5 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Schutzinstallationen Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25



Surge arrester V20, 4-pole, 280 V



Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4-280	280	4	IP20	1	47.000	5095164


Surge arrester, type 2


- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.


V20-4-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





Surge arrester V20, 4-pole with remote signaling, 280 V




Surge arrester, type 2

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular connectable arrester with cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic to UL 94 V-0
- The remote signalling variants (FS) have a potential-free changeover contact for remote signalling

Application: Equipotential bonding in main and sub-distributions.

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-4+FS-280	280	4	IP20	1	47.500	5095284

Connection options




V20-4+FS-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 160 kA
Protection level [L-N]	U_b 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,8 kV
Residual voltage [L-N] @ 5 kA	U_{res} 1,0 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP20
Approvals	UL, ÖVE, VDE, KEMA
FM contacts	Changeover
Switching power AC	230 V; 0,5 A
Switching power DC	230 V; 0,1 A / 75 V; 0,5 A
Connection cross-section, FM terminals	0,5 - 1,5 mm ²
Connection cross-section, FM terminals	21 - 16 AWG
Conductor cross-section, flexible (fine-wire)	1,5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1,5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Schutzinstalltionen: Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25



Surge arrester V10 Compact 255 V



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT 255	255	3 + NPE	1	15.800	5093380

Surge protection device, compact module, type 2+3


- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Incl. thermal and dynamic cut-off unit and visual function display

Application: Sub/storey distribution as well as device protection in rotational current systems.

V10 COMPACT 255


Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_d	< 1,1 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²

Connection options





Surge arrester V10 Compact with audible signalling 255 V




Surge protective device, compact module, type 2+3

- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Including thermic and dynamic cut-off unit and visual function display
- ...-AS version with additional acoustic defect signalling (switchable)

Application: Sub/storey distribution as well as device protection in rotational current systems.

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT-AS	255	3+NPE	1	15.800	5093391


Connection options



V10 COMPACT-AS		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→3
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	< 1,1 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		63 A
Temperature range	ϑ	-40 - +80 °C
Division unit TE (17.5 mm)		1.5
Protection rating		IP20
Connection cross-section, rigid		2.5 - 10 mm ²
Connection cross-section, multi-wire		2.5 - 10 mm ²
Connection cross-section, flexible		2.5 - 10 mm ²



Surge arrester V10 Compact with remote signalling 255 V



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V10 COMPACT-FS	255	3+NPE	1	17.300	5093382


Surge protective device, compact module, type 2+3

- Surge protection in sub-distributors to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 60 kA (8/20) in total
- Integrated 3+1 solution for TN and TT network systems on 45 mm module width
- High-performance varistor technology
- Including thermic and dynamic cut-off unit and visual function display
- ...-FS version with potential-free changeover contact for remote signalling

Application: Sub/storey distribution as well as device protection in rotational current systems.


V10 COMPACT-FS			
Nominal voltage	U_N	230 V	
Max. continuous operating voltage	U_C	255 V	
SPD to EN 61643-11		Type 2+3	
SPD to IEC 61643-11		Class II+III	
Lightning protection zone LPZ		1→3	
Nominal discharge current (8/20)	I_n	10 kA	
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	60 kA	
Maximum discharge current (8/20 μ s)	I_{max}	20 kA	
Protection level	U_p	< 1,1 kV	
Response time	t_A	< 25 ns	
Maximum back-up fuse		63 A	
Temperature range	ϑ	-40 - +80 °C	
Division unit TE (17.5 mm)		1.5	
Protection rating		IP20	
Connection cross-section, rigid		2.5 - 10 mm ²	
Connection cross-section, multi-wire		2.5 - 10 mm ²	
Connection cross-section, flexible		2.5 - 10 mm ²	

Connection options





Combination arrester V50, 1-pole + NPE 280 V




Lightning current combination arrester, type 1+2 to DIN EN 61643-11

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Complete unit, pre-mounted and ready for connection in polycarbonate housing (IP66)
- Lightning current arresting capacity 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total

Application: Lightning protection equipotential bonding for buildings of Class III and IV.
If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	Max. continuous voltage AC V	Pole version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V50-1+NPE-280	280	1+N/PE	1	81.000	5093594


Connection options



VG-V50-1+NPE-280	
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I-II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 25 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 50 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP66
Approvals	UL, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



Combination arrester V50, 3-pole + NPE 280 V



Type	Max. continuous voltage AC V	Pole version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V50-3+NPE-280	280	3+N/PE	1	110.000	5093596

Lightning current combination arrester, type 1+2 to DIN EN 61643-11

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Complete unit, pre-mounted and ready for connection in polycarbonate housing (IP66)
- Lightning current arresting capacity 12.5 kA (10/350) per pole and up to 50 kA (10/350) in total


Application: Lightning protection equipotential bonding for buildings of Class III and IV.

If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-V50-3+NPE-280



SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_C 280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$ 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 50 kA
Lightning surge current (10/350 μ s)	I_{imp} 12.5 kA
Lightning surge current (10/350)	I_{total} 50 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 50 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,8 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP66
Approvals	UL, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG

Connection options





VG housing with MCD 50-B/3+1



Combination arrester, pre-installed in IP65 housing for use in TN-S and TT networks.


VG...: Lightning arrester system solution type 1+2 according to DIN EN 61643-11.

- LightningController MCD 50-B and MCD 125-B/NPE mounted in insulating housing IP65, sealable housing
- Pulse current 125 kA (10/350 μ s), BET-tested
- Conforms to requirements of VDE-AR-N 4100
- Protection level < 1.7 kV (L-N) and < 1.5 kV (N-PE)
- Encapsulated, non-extinguishing discharge gap
- Suitable for TN-S and TT network systems

Application example: The system solution is used in the pre-meter area according to VDE-AR-N 4100.

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3+1-VG	255	3+NPE	1	290.000	5096875

Connection options





MCD 50-B 3+1-VG

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	125 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	125 kA
Protection level	U_p	< 1,7 kV
Protection level (N-PE)		< 1,5 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi eff}$	10 kA
Follow current quenching capacity (eff) [N-PE]	I_{fi}	25 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		8
Protection rating		IP54
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²



VG housing with MCD 50-B/3



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCD 50-B 3-VG	255	3-pole	1	315.000	5096874

Combination arrester, pre-installed in IP65 housing for use in TN-C networks.

VG...: Combination arrester system solution, type 1+2, according to EN 61643-11.


- LightningController MCD 50-B mounted in insulating housing IP 65, sealable housing
- Pulse current 150 kA 10/350 μ s / 50 kA (10/350) per pole, BET-tested
- Protection level < 1.7 kV
- Encapsulated, non-extinguishing spark gaps
- Suitable for TN-C network systems

Application example: The system solution is used in the pre-meter area according to VDE-AR-N 4100.

MCD 50-B 3-VG


Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	150 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	150 kA
Protection level	U_p	< 1,7 kV
Response time	t_A	<100 ns
Follow current quenching capacity I_{fi}	$I_{fi eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		6
Protection rating		IP54
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Connection options





System solution, surge arrester V20 in housing, 1-pole + NPE, 280 V




Surge arrester, type 2, according DIN EN 61643-11

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Complete unit, pre-mounted and ready for connection in polycarbonate housing (IP66)
- Arresting capacity to 40 kA (8/20) per pole through high-performance varistors

Application: Equipotential bonding in main and sub-distributors. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	Max. continuous voltage AC V	Pole version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V20-1+NPE-280	280	1+N/PE	1	74.000	5095381

Connection options




VG-V20-1+NPE-280	
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
SPD to UL 1449	Type 4
Nominal voltage AC (50/60 Hz)	U_n 230 V
Maximum continuous voltage AC	U_c 280 V
Nominal discharge current (8/20 μ s)	$I_{n/L-N}$ 20 kA
Maximum discharge current (8/20 μ s)	I_{max} 40 kA
Arrester surge current (8/20 μ s) [total]	I_{total} 60 kA
Protection level [L-N]	U_p 1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res} 0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res} 0,9 kV
Max. mains-side overcurrent protection	160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection	50 kA eff
Operating temperature range	T_u -40 - +80 °C
Protection rating	IP66
Approvals	ÖVE, UL
Conductor cross-section, flexible (fine-wire)	1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)	1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)	16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)	16 - 2 AWG



System solution, surge arrester V20 in housing, 3-pole + NPE, 280 V

Surge protection



Type	Max. continuous voltage V	Pole version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V20-3+NPE-280	280	3+N/PE	1	96.000	5095383


Surge arrester, type 2, according to DIN EN 61643-11

- For surge voltage protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Complete unit, pre-mounted and ready for connection in polycarbonate housing (IP66)
- Arresting capacity to 40 kA (8/20) per pole through high-performance varistors

Application: Equipotential bonding in main and sub-distributors. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-V20-3+NPE-280		Type 2
SPD to EN 61643-11		Class II
SPD to IEC 61643-11		Type 4
SPD to UL 1449		
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_C	280 V
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	40 kA
Arrester surge current (8/20 μ s) [total]	I_{total}	60 kA
Protection level [L-N]	U_D	1.3 kV
Residual voltage [L-N] @ 1 kA	U_{res}	0,7 kV
Residual voltage [L-N] @ 5 kA	U_{res}	0,9 kV
Max. mains-side overcurrent protection		160 A gL/gG
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP66
Approvals		ÖVE, UL
Conductor cross-section, flexible (fine-wire)		1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)		16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)		16 - 2 AWG

Connection options



Compact surge protection

Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids to protect LED lighting and/or the LED driver.

Application in:

- Cable fuse box in the street lighting pole
- Junction boxes
- Cable ducts
- Underfloor systems
- Electrical equipment




Surge protective devices type 2+3

- With function display and switch-off of the load current circuit should the SPD fail
- Small construction size for installation in the pole connection box or in front of the driver
- Reduction of the surge voltage to below 1,300 V (protection level)
- Optionally available as IP65 version



Surge protection for LED systems ÜSM-20-230I1P+PE

Surge protection



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-20-230I1P+PE	255	1-pole + NPE for PCI	1	4.100	5092431


Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of LED lighting.

- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Reduction of overvoltage to under 1,300 V or 1,000 V @ 5 kA
- With or without luminaire switch-off in case of defect

Application: In the cable transition box, junction boxes, cable duct to underfloor systems


ÜSM-20-230I1P+PE			
Nominal voltage	U_N		230 V
Max. continuous operating voltage	U_C		255 V
SPD to EN 61643-11			Type 2+3
SPD to IEC 61643-11			Class II+III
Lightning protection zone LPZ			1→2
Nominal discharge current (8/20)	I_n		10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$		20 kA
Maximum discharge current (8/20 μ s)	I_{max}		20 kA
Protection level	U_p		1,3 kV
Response time	t_A		< 25 ns
Maximum back-up fuse			16 A
Operating temperature range	T_u		-40 - +80 °C
Protection rating			IP20
Connecting cable length			0.09 m

Connection options





Surge protection for LED systems ÜSM-20-2301PE65




Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of LED lighting.

- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- 1+NPE protective circuit with a maximum discharge capacity of 20 kA
- Reduction of overvoltage to under 1,500 V or 1,000 V @ 5 kA
- With or without luminaire switch-off in case of defect

Application: In the cable transition box, junction boxes, cable ducts to underfloor systems

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-20-2301PE65	255	1-pole + NPE for PCI	1	8.300	5092433


Connection options



ÜSM-20-2301PE65		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	10 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	20 kA
Protection level	U_p	1,5 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP65
Connecting cable length		0.25 m



Surge protection module ÜSM-10-230I1P+PE



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I1P+PE	255	1-pole + NPE for PCI	1	3.500	5092422


Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of electronic devices and LED drivers.

- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Use in the LED luminaire head upstream of the electronic LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For LED luminaires with PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems


ÜSM-10-230I1P+PE		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	10 kA
Maximum discharge current (8/20 µs)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Connection options





Surge protection module ÜSM-10-230I1P-0




Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of electronic devices and LED drivers.

- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For protection insulated luminaires (PC II) without PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I1P-0	255	1-pole without NPE for PC II	1	3.200	5092420


Connection options



ÜSM-10-230I1P-0		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1-2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	— kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_o	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m



Surge protection module ÜSM-10-230I2P+PE



Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I2P+PE	255	2-pole + NPE for PCI	1	4.400	5092426


Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of electronic devices and LED drivers.

- For luminaires with 2 phases (power reduction)
- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For LED luminaires with PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems


ÜSM-10-230I2P+PE		
Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	10 kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m

Connection options





Surge protection module ÜSM-10-230I2P-0




Surge protection module type 2+3 to DIN EN 61643-11 for 230/400 V power grids. Appropriate for the protection of electronic devices and LED drivers.

- For luminaires with 2 phases (power reduction)
- With function display and switch-off of the load circuit when an SPD fails
- Small size for the installation in the pole connection box or upstream of the LED driver
- Protective circuit with a maximum arresting capacity of 10 kA
- Reduction of overvoltage to under 1,300 V (protection level)
- For protection insulated luminaires (PC II) without PE connection

Application: In the cable transition box, junction boxes, cable duct to underfloor systems

Type	Highest continuous voltage V	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-10-230I2P-0	255	2-pole without NPE for SK II	1	4.100	5092424

Connection options




ÜSM-10-230I2P-0

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 2+3
SPD to IEC 61643-11		Class II+III
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I_n	5 kA
Arrestor surge current (8/20) [total]	$I_{Total\ 8/20}$	— kA
Maximum discharge current (8/20 μ s)	I_{max}	10 kA
Protection level	U_p	1,3 kV
Response time	t_A	< 25 ns
Maximum back-up fuse		16 A
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Connecting cable length		0.09 m



Surge protection module 230 V



Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-A	Acoustic	Acoustic operating display	1	1.500	5092451


Surge protection module type 3 to DIN EN 61643-11 for 230 V power grids.

- With audible defect signal
- With low construction height
- Halogen-free plastic (UL 94 V-0)
- Y circuit

Application: Universally applicable for all installation systems.



ÜSM-A	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 255 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I_n 3 kA
Protection level (L-N)	< 1,3 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A < 25 ns
Temperature range	ϑ -15 - +60 °C
Maximum discharge current (8/20 µs)	I_{max} 6 kA
Rated current	I_L 16 A

Connection options





Fine power protection 230 V protective contact sockets




Surge protection / fine power protection, type 3, to EN 61643-11 for protective contact sockets.

- Thermal cut-off unit with acoustic defect signalling
- Y protection circuit for increased safety
- Mounting through snapping onto the support ring of the socket
- Halogen-free plastic (UL 94 V-0)
- Labelling of the socket with supplied sign

Application: For retrofitting on standard Schuko sockets.

Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-ST-230-1P+PE	Acoustic	Acoustic function display	1	1.770	5092441



Connection options



ÜSM-ST-230-1P+PE	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 255 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2-3
Nominal discharge current (8/20)	I_n 3 kA
Maximum discharge current (8/20 μ s)	I_{max} 5 kA
Protection level (L-N)	< 1,5 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A 25 ns
Temperature range	ϑ -5 - +40 °C



Surge protection module 230 V with holder for GB2 and GB3 mounting boxes



Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-A-4	Acoustic	Incl. holder with partition function	1	2.000	5092472


Surge protection module type 3 to DIN EN 61643-11 for 230 V power grids.

- With acoustic defect signal
- With low construction height and Y circuit
- With halogen-free plastic (UL 94 V-0)
- Holder with separating retainer function for GB2 / GB3 mounting boxes and UT3 and UT4 universal supports

Application: Universally applicable for all installation systems.


ÜSM-A-4	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 255 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I_n 3 kA
Maximum discharge current (8/20 μ s)	I_{max} 6 kA
Protection level (L-N)	< 1,3 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A < 25 ns
Temperature range	ϑ -15 - +60 °C

Connection options





Surge protective device 230 V for through wiring




Surge protective device type 3 to DIN EN 61643-11 for 230 V networks.

- With acoustic defect signal
- With 2 strands for continuous wiring
- With low construction height
- Halogen-free plastic (UL 94 V-0)
- Y circuit

Application: Universally applicable for all installation systems.

Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSM-A-2	Acoustic	V connection	1	2.200	5092460

Connection options




ÜSM-A-2

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1,3 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	< 25 ns
Temperature range	ϑ	-15 - +60 °C
Maximum discharge current (8/20 μ s)	I_{max}	6 kA
Rated current	I_L	16 A



Fine power protection for Modul 45 with acoustic function display



Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSS 45-O-RW	Visual	Visual function display	1	2.411	6117473

Surge protection / network fine protection, type 3, according to EN 61643-11 for installation in Rapid 45 trunking, device installation trunking and underfloor systems.


- Version-O with acoustic function display
- Quick and easy mounting
- Low construction width of 22.5 mm
- Colour: Pure white; RAL 9010

Application: The surge protective device secures downstream and nearby sockets.

ÜSS 45-O-RW



Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2-3
Nominal discharge current (8/20)	I_n	2.5 kA
Protection level (L-N)		< 1,5 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	25 ns
Temperature range	ϑ	-25 - +45 °C

Connection options





Surge protection module for Modul 45 with audible signalling




Surge protection / network fine protection, type 3, according to EN 61643-11 for installation in Rapid 45 trunking, device installation trunking and underfloor systems.

- Version-A with acoustic function display (switchable signal tone)
- Quick and easy mounting
- Low construction width of 22.5 mm
- Colour: Pure white; RAL 9010

Application: The surge protection device secures downstream and nearby sockets.

Type	Signalling on device	Version	Pack Piece	Weight kg/100 pc.	Item no.
ÜSS 45-A-RW	Acoustic	Acoustic function display	1	2.800	6117465


Connection options



ÜSS 45-A-RW	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 255 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I_n 2.5 kA
Protection level (L-N)	< 1,5 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A 25 ns
Temperature range	ϑ -25 - +45 °C



FineController FC-SAT for SAT systems and receivers



Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-SAT-D	EN	Pure white	1	16.000	5092816


Type 3 combined surge protection to EN 61643-11, designed for use on satellite systems and receivers.

- Adapter connector
- Cut-off unit and function display
- With increased contact protection
- Incl. 0.5 m connection cable in white (double-shielded)
- Maximum continuous voltage, TV connection 72 V DC / 1.5 A (25 °C)
- Limit frequency: type 2.5 GHz (75 Ohm system)

Note: The technical data in the table below refers to the power supply.


FC-SAT-D	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 275 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I_n 3 kA
Protection level (L-N)	< 1,2 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A <25 ns

Connection options





FineController FC-D for protective contact socket




Type 3 surge protective device to EN 61643-11, intended for use in protective contact sockets.

- Adapter connector
- Cut-off unit and function display
- With increased touch protection

Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-D	EN	Pure white	1	11.000	5092800

Connection options




FC-D

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	275 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1,2 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	<25 ns



FineController FC-TAE for telephone systems and terminals



Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-TAE-D	EN	Pure white	1	18.000	5092824


Type 3 combined surge protection to EN 61643-11, designed for use in telephone systems with TAE connection (telephones upstream of the NTBA/DSL splitter).

- Adapter connector
- Cut-off unit and function display
- With increased contact protection
- Incl. 0.5 m connection cable TAE / RJ11
- Maximum continuous voltage, TAE connection 200 V DC / 1.5 A (25 °C)
- Limit frequency: type 4 MHz / VDSL up to 46 MBit/s

Note: The technical data in the table below refers to the power supply.


FC-TAE-D	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 275 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I_n 3 kA
Protection level (L-N)	< 1,2 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A <25 ns

Connection options





FineController FC-TV for video, TV and hi-fi systems




Type 3 combined surge protection to EN 61643-11, designed for use on Schuko sockets and video, TV and hi-fi systems with IEC adapter.

- Adapter connector
- Cut-off unit and function display
- With increased contact protection
- Incl. 0.5 m connection cable in white (double-shielded)
- Maximum continuous voltage, TV connection 72 V DC / 1.5 A (25 °C)
- Limit frequency: type 2.5 GHz (75 Ohm system)

Note: The technical data in the table below refers to the power supply.

Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-TV-D	EN	Pure white	1	17.000	5092808

Connection options




FC-TV-D

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	275 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1,2 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	<25 ns



FineController FC-ISDN for ISDN telephone systems and terminals



Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-ISDN-D	EN	Pure white	1	18.000	5092812


Type 3 combined surge protection to EN 61643-11 designed for use in ISDN / DSS 1 telephone systems and terminals.

- Adapter connector
- Cut-off unit and function display
- With increased contact protection
- Incl. 0.5 m connection cable RJ12
- Maximum continuous voltage, ISDN connection 6 V DC / 1.5 A (25 °C)
- Limit frequency: type 300 kHz

Note: The technical data in the table below refers to the power supply.


FC-ISDN-D	
Nominal voltage	U_N 230 V
Max. continuous operating voltage	U_C 275 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2-3
Nominal discharge current (8/20)	I_n 3 kA
Protection level (L-N)	< 1,2 kV
Protection level (N-PE)	< 1,5 kV
Maximum back-up fuse	16 A
Response time	t_A <25 ns

Connection options





FineController FC-RJ-D for telephone systems with RJ12




Type 3 combined surge protection to EN 61643-11 designed for use in telephone systems and terminals with RJ12 connection.

- Adapter connector
- Cut-off unit and function display
- With increased contact protection
- Incl. 0.5 m connection cable RJ12
- Maximum continuous voltage, RJ connection 200 V DC / 1.5 A (25 °C)
- Limit frequency: type 4 MHz / DSL-compatible

Note: The technical data in the table below refers to the power supply.

Type	Country version	Colour	Pack Piece	Weight kg/100 pc.	Item no.
FC-RJ-D	EN	Pure white	1	18.000	5092828

Connection options




FC-RJ-D

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	275 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	3 kA
Protection level (L-N)		< 1,2 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	<25 ns



Surge protective device CNS 3 D



Type	Country version	Colour	Connection cable length m	Pack Piece	Weight kg/100 pc.	Item no.
CNS 3-D-D	EN	Black	2	1	65.000	5092701

Surge protective device, type 3, to DIN EN 61643-11, intended for use in protective contact sockets.


- With visual and audible signalling, function display
- 3-way socket
- Length of connection cable: 2 m
- Y circuit for high electrical safety


Application: For example, the protection of PCs, printers, copiers, fax machines, etc.

CNS 3-D-D

Nominal voltage	U_N	230 V
Max. continuous operating voltage	U_C	255 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	2.5 kA
Protection level (L-N)		< 1,0 kV
Protection level (N-PE)		< 1,5 kV
Maximum back-up fuse		16 A
Response time	t_A	<25 ns

Connection options





FRD/FLD family

Basic and combination protection for two-core systems




- High arresting capacity
- Low noise
- Universal application
- Simple mounting using screwless terminals
- High bandwidth
- UL-listed

The use of lightning barriers in two-core wire systems is commonplace. These surge protective devices are used from telecommunication cables through bus systems up to measurement and control technology. Surge protection technology allows flexible protection for all kinds of applications. All the devices have both a low protection level and a high arresting capacity.



Combination protection for two-core systems with HF applications 5 V




Surge protection for use in measuring, control and regulation systems.

- Basic, medium and fine protection
- Two-stage protection circuit with high lightning current carrying capacity
- High transmission frequency up to 100 MHz
- Suitable for all bus systems (e.g. Profibus)
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid

Application: Multipurpose use on any 35 mm DIN profile rail in every commercially available distribution housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 5 HF	4	6	2	Terminal	1	4.400	5098571

Connection options



FRD 5 HF	
Maximum continuous voltage AC	U_c 4 V
Maximum continuous voltage DC	U_c 6 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.45 A
Series resistance per wire	2,2 Ω \pm 10 %
Impulse durability wire-wire	C2: 18 kV / 9 kA (8/20 μ s)
Impulse durability wire-earth	C2: 18 kV / 9 kA (8/20 μ s)
Total discharge current (8/20)	18 kA
Total discharge current (10/350)	D1: 6 kA
Protection level wire-wire	<90 V
Protection level wire-earth	<650 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Combination protection for two-core systems with HF applications 24 V



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 24 HF	19	28	2	Terminal	1	4.400	5098575


Surge protection for use in measuring, control and regulation systems.

- Basic, medium and fine protection
- Two-stage protection circuit with high lightning current carrying capacity
- High transmission frequency up to 100 MHz
- Suitable for all bus systems (e.g. Profibus)
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid

Application: Multipurpose use on any 35 mm DIN profile rail in every commercially available distribution housing.


FRD 24 HF	
Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_L 0.45 A
Series resistance per wire	2,2 $\Omega \pm 10\%$
Impulse durability wire-wire	C2: 18 kV / 9 kA (8/20 μ s)
Impulse durability wire-earth	C2: 18 kV / 9 kA (8/20 μ s)
Total discharge current (8/20)	18 kA
Total discharge current (10/350)	D1: 6 kA
Protection level wire-wire	<120 V
Protection level wire-earth	<650 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Basic protection for two-core systems with HF applications 120 V




TKS-B: Surge protection for use in measuring, control and regulation systems, as well as telecommunication systems

- Basic protection for lightning protection equipotential bonding
 - High impulse arresting capacity 6 kA (10/350)
 - With installation-friendly, screwless connection terminals
 - In space-saving 17.5 mm grid
- Application: Universal use on 35 mm hat profile rail in any standard distributor housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TKS-B	120	170	2	Terminal	1	4.400	5097976

Connection options



TKS-B	
Maximum continuous voltage AC	U_C 120 V
Maximum continuous voltage DC	U_C 170 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0→2
Number of poles	2
Rated current	I_L 20 A
Impulse durability wire-wire	C2: 18 kV / 9 kA
Impulse durability wire-earth	C2: 18 kV / 9 kA
Total discharge current (8/20)	18 kA
Total discharge current (10/350)	D1: 6 kA
Protection level wire-wire	<950 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Connection cable
Testing standard	IEC 61643-21

Medium and fine protection FRD for two-core systems 24 V



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 24	19	28	2	Terminal	1	5.100	5098514


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


FRD 24	
Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.2 A
Series resistance per wire	15 Ω ± 10 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<60 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Medium and fine protection FRD for two-core systems 48 V




Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 48	37	53	2	Terminal	1	5.100	5098522

Connection options



FRD 48	
Maximum continuous voltage AC	U_c 37 V
Maximum continuous voltage DC	U_c 53 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.2 A
Series resistance per wire	15 Ω \pm 10 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<140 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FRD for two-core systems 110 V



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FRD 110	86	122	2	Terminal	1	5.100	5098557


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for double core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With ohmic decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


FRD 110	
Maximum continuous voltage AC	U_c 86 V
Maximum continuous voltage DC	U_c 122 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.2 A
Series resistance per wire	15 Ω \pm 10 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Medium and fine protection FLD for two-core systems 5 V




Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 5	5	8	2	Terminal	1	5.200	5098600

Connection options



FLD 5	
Maximum continuous voltage AC	U_c 5 V
Maximum continuous voltage DC	U_c 8 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<15 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FLD for two-core systems 12 V



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 12	9	13	2	Terminal	1	5.200	5098603


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


FLD 12	
Maximum continuous voltage AC	U_c 9 V
Maximum continuous voltage DC	U_c 13 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<30 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Medium and fine protection FLD for two-core systems 24 V




Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 24	19	28	2	Terminal	1	5.200	5098611

Connection options



FLD 24	
Maximum continuous voltage AC	U_c 19 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<60 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Medium and fine protection FLD for two-core systems 48 V



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 48	37	53	2	Terminal	1	5.200	5098630


Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.


FLD 48	
Maximum continuous voltage AC	U_c 37 V
Maximum continuous voltage DC	U_c 53 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C2: 5 kV / 2,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<140 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Medium and fine protection FLD for two-core systems 110 V




Surge protection for use in measurement and control technology

- Medium and fine protection
- Standard design for single core systems
- Two-stage protection circuit
- With installation-friendly, screwless connection terminals
- In space-saving 17.5 mm grid
- With inductive decoupling in the longitudinal branch

Application: Universal use on any 35 mm DIN profile rail in every commercially available distributor housing.

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
FLD 110	86	122	2	Terminal	1	5.200	5098646

Connection options



FLD 110	
Maximum continuous voltage AC	U_c 86 V
Maximum continuous voltage DC	U_c 122 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 1 A
Series inductivity per wire	120 μ H \pm 20 %
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 3 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Division unit TE (17.5 mm)	1
Protection rating	IP20
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	Terminal
Testing standard	IEC 61643-21
Approvals	UL

MDP family

MCR protection for multi-wire systems (testable)




- Protection device for multi-wire systems (4-pole)
- Direct shield earthing
- Easy-mounting, screwless connection terminals
- Space-saving width of just 8.7 mm
- Versions with nominal currents up to 10 A
- High frequency bandwidth up to 100 MHz
- UL-listed

Besides the high current capacity, the lightning barriers of type MDP offer a narrow installation width of just 8.7 mm. A separate screen connection permits screen attachment on both sides of the equipotential bonding, thus optimising the screen effect against capacitive and inductive couplings. Depen-

ding on the version, a nominal current of up to 10 A can be applied to the devices, meaning that they are thus ideally suited to use in special applications, such as slip ring transmitters or heating systems in wind power systems. When installed, all the MDPs can be checked using LifeControl.



MCR protection for 2-pole power supply, 12 V




Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.

Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF12-AC DC	13.5	1	9.000	5097453


Connection options



VF12-AC DC

U max AC	U _c AC	13.5 V
U max DC	U _c DC	18 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I _n	0,7 kA
Maximum discharge current (8/20 μs)	I _{max}	2 kA
Rated current	I _L	20 A
Protection level wire-wire		<110 V
Protection level wire-earth		<1200 V
Response time	t _A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

MCR protection for 2-pole for power supply, 24 V



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF24-AC/DC	34	1	8.000	5097607


Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.


VF24-AC/DC	
U max AC	U _c AC 34 V
U max DC	U _c DC 46 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2-3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<130 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

Connection options





MCR protection for 2-pole for power supply, 48 V




Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.


Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF48-AC/DC	60	1	8.000	5097615

Connection options



VF48-AC/DC	
U max AC	U _c AC 60 V
U max DC	U _c DC 80 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<220 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

MCR protection for 2-pole for power supply, 60 V



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF60-AC/DC	80	1	8.000	5097623


Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.


VF60-AC/DC	
U max AC	U _c AC 80 V
U max DC	U _c DC 110 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<280 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

Connection options





MCR protection for 2-pole for power supply, 110 V




Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.


Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF110-AC DC	150	1	8.000	5097631

Connection options



VF110-AC DC	
U max AC	U _c AC 150 V
U max DC	U _c DC 200 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 2 kA
Maximum discharge current (8/20 μs)	I _{max} 6.5 kA
Rated current	I _L 20 A
Protection level wire-wire	<500 V
Protection level wire-earth	<1400 V
Response time	t _A <25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

MCR protection for 2-pole for power supply, 230 V



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF230-AC/DC	255	1	8.000	5097650


Surge protection device/fine protection type 3 to EN 61643-11

- Suitable for DC and AC voltage systems
- With visual function display
- With installation-friendly, screwless connection terminals
- In a space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rail in every normal commercially available distributor housing.


VF230-AC/DC	
U max AC	U _c AC 255 V
U max DC	U _c DC 350 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2-3
Nominal discharge current (8/20)	I _n 2.5 kA
Maximum discharge current (8/20 μs)	I _{max} 7 kA
Rated current	I _L 20 A
Protection level wire-wire	<1000 V
Protection level wire-earth	<1400 V
Response time	t _A <25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

Connection options





MCR protection for 2-pole for power supply with remote signalling, 12 V AC/DC




Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.


Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF12-AC/DC-FS	13.5	1	6.400	5097454

Connection options



VF12-AC/DC-FS	
U max AC	U _c AC 13.5 V
U max DC	U _c DC 18 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<110 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

MCR protection for 2-pole power supply with remote signalling, 24 V AC/DC



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF24-AC/DC-FS	34	1	6.620	5097820


Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.


VF24-AC/DC-FS	
U max AC	U _c AC 34 V
U max DC	U _c DC 46 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<160 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

Connection options





MMSR protection for 2-pole power supply with remote signalling, 48 V AC/DC




Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for DC and AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.


Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF48-AC/DC-FS	60	1	6.630	5097822

Connection options



VF48-AC/DC-FS	
U max AC	U _{c AC} 60 V
U max DC	U _{c DC} 80 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 0,7 kA
Maximum discharge current (8/20 μs)	I _{max} 2 kA
Rated current	I _L 20 A
Protection level wire-wire	<220 V
Protection level wire-earth	<1200 V
Response time	t _A <25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

MCR protection for 2-pole power supply with remote signalling, 230 V AC



Type	Highest continuous voltage V	Pack Piece	Weight kg/100 pc.	Item no.
VF230-AC-FS	255	1	6.910	5097858


Surge protection / fine power protection, type 3, to EN 61643-11 with remote signalling

- With remote signalling, potential-free changeover contact, for function monitoring
- Suitable for AC systems
- With visual function display
- With easy mounting, screwless connection terminals
- In space-saving 17.5 mm grid
- Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.


VF230-AC-FS	
U max AC	U _c AC 255 V
SPD to EN 61643-11	Type 3
SPD to IEC 61643-11	Class III
Lightning protection zone LPZ	2→3
Nominal discharge current (8/20)	I _n 2,5 kA
Maximum discharge current (8/20 μs)	I _{max} 7 kA
Rated current	I _L 20 A
Protection level wire-wire	<1060 V
Protection level wire-earth	<1400 V
Response time	t _A <25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1
Connection cross-section, rigid	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, flexible	0.14 - 2.5 mm ²

Connection options





MCR protection for 2-pin for power supply with leak current-free remote signalling, 230 V AC/DC




- Type 3 surge protection/fine network protection to EN 61643-11 with leak current-free remote signalling
- With remote signalling: potential-free NC contact for function monitoring
 - With installation-friendly, screwless connection terminals
 - In space-saving 17.5 mm grid
 - Y circuit

Application: Universal use on 35 mm DIN profile rails in any standard distributor housing.

Type	U max		Pack Piece	Weight kg/100 pc.	Item no.
	AC V	DC V			
VF2-230-AC/DC-FS	255	350	1	6.000	5097939

Connection options



VF2-230-AC/DC-FS		
U max AC	U_c AC	255 V
U max DC	U_c DC	350 V
SPD to EN 61643-11		Type 3
SPD to IEC 61643-11		Class III
Lightning protection zone LPZ		2→3
Nominal discharge current (8/20)	I_n	2,5 kA
Maximum discharge current (8/20 μ s)	I_{max}	7 kA
Rated current	I_L	20 A
Protection level wire-wire		< 1000 V
Protection level wire-earth		< 1400 V
Response time	t_A	<25 ns
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1
Connection cross-section, rigid		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 2.5 mm ²
Connection cross-section, flexible		0.14 - 2.5 mm ²

VF family

Protection for 2-pin power supplies




- High arresting capacity
- Low noise level
- Usable in AC/DC applications
- Simple mounting using screwless terminals

The lightning barriers of type VF are fine protection devices, used for single-phase energy technology systems. Besides the low protection level, these devices also have a visual display, which will indicate defective surge protection. If required, remote signalling is also available using a changeover contact and an NC contact.



Series protection device, 2-pole, 5 V version




Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-5-T	7	10	2	Terminal	1	6.000	5098404

Connection options



MDP-2 D-5-T	
Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<35 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 3-pole, 5 V version



Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-5-T	7	10	3	Terminal	1	6.000	5098407


Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


MDP-3 D-5-T	
Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	3
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	7,5 kA
Total discharge current (10/350)	D1: 1,5 kA
Protection level wire-wire	<35 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 4-pole, 5 V version




Lightning barrier with test function; 5 V version

- Nominal load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High frequency range of 0–100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-T	7	10	4	Terminal	1	6.000	5098411

Connection options



MDP-4 D-5-T	
Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<35 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 2-pole, 24 V version



Surge protection

Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-24-T	20	28	2	Terminal	1	6.000	5098422


Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


MDP-2 D-24-T	
Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.58 A
Series resistance per wire	2,35 $\Omega \pm 5\%$
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 3-pole, 24 V version




Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-24-T	20	28	3	Terminal	1	6.000	5098427

Connection options



MDP-3 D-24-T	
Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	3
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	7,5 kA
Total discharge current (10/350)	D1: 1,5 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 24 V version



Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-24-T	20	28	4	Terminal	1	5.800	5098431


Lightning barrier with test function; 24 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


MDP-4 D-24-T	
Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 2-pole, 48 V version




Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-48-T	41	58	2	Terminal	1	6.000	5098442

Connection options



MDP-2 D-48-T	
Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<95 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 3-pole, 48 V version



Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-3 D-48-T	41	58	3	Terminal	1	6.000	5098446


Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


MDP-3 D-48-T	
Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	3
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	7,5 kA
Total discharge current (10/350)	D1: 1,5 kA
Protection level wire-wire	<95 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 4-pole, 48 V version




Lightning barrier with test function; 48 V version

- Rated load current 0.58 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-48-T	41	58	4	Terminal	1	5.800	5098450

Connection options



MDP-4 D-48-T	
Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	4
Rated current	I_L 0.58 A
Series resistance per wire	2,35 Ω \pm 5 %
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<95 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 5 V version



Surge protection

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-T-10	7	10	4	Terminal	1	7.200	5098413


Lightning barrier with test function; 5 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN rail in any standard distribution housing.


MDP-4 D-5-T-10	
Maximum continuous voltage AC	U_c 7 V
Maximum continuous voltage DC	U_c 10 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_L 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<45 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 2-pole, 12 V version




Lightning barrier with test function; 12 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-12-T-10	10.5	15	2	Terminal	1	6.000	5098415

Connection options



MDP-2 D-12-T-10	
Maximum continuous voltage AC	U_c 10.5 V
Maximum continuous voltage DC	U_c 15 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Series protection device, 4-pole, 12 V version



Surge protection

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-12-T-10	10.5	15	4	Terminal	1	6.000	5098419


Lightning barrier with test function; 12 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


MDP-4 D-12-T-10	
Maximum continuous voltage AC	U_c 10.5 V
Maximum continuous voltage DC	U_c 15 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_L 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 2 kA
Protection level wire-wire	<55 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connection options





Series protection device, 2-pole, 24 V version




Lightning barrier with test function; 24 V version

- Rated load current 10 A
- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- Protection circuit testable with Life Control
- High bandwidth to 100 MHz
- UL-listed (4DG1)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.


Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
MDP-2 D-24-T-10	20	28	2	Terminal	1	6.000	5098425

Connection options



MDP-2 D-24-T-10	
Maximum continuous voltage AC	U_c 20 V
Maximum continuous voltage DC	U_c 28 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	2
Rated current	I_L 10 A
Series resistance per wire	—
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Total discharge current (10/350)	D1: 1 kA
Protection level wire-wire	<70 V
Protection level wire-earth	<800 V
Frequency range	0 - 100 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail
Connection system	Terminal
Protection rating	IP20
Shielding connection available	Yes
Shield connection	Direct
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 1.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Earthing via:	DIN rail
Testing standard	IEC 61643-21
Approvals	UL

Connectable data cable protection, 2-pole, direct earthing



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-5-D	4.2	6	2	1	6.500	5080301
PDP-2-12-D	12	16	2	1	6.500	5080303
PDP-2-24-D	21	30	2	1	6.500	5080305
PDP-2-48-D	37	52	2	1	6.500	5080307


Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Direct shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Installation width from 12.5 mm
- High system availability – no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.



Connectable data cable protection, 2-pole, indirect earthing



Connectable data cable protection, type 1+2/D1+C2 for use in measurement and control technology

- Protection device for multi-wire systems
- Indirect shield earthing
- Frequency range up to 100 MHz
- Earthing via DIN rail or connection cable
- Small installation width of 12.5 mm
- High system availability - no signal interruption without protection module

Application: Universal lightning and surge protection for MCR data transmission devices.

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
PDP-2-5-I	4.2	6	2	1	6.600	5080309
PDP-2-12-I	12	16	2	1	6.600	5080311
PDP-2-24-I	21	30	2	1	6.600	5080313
PDP-2-48-I	37	52	2	1	6.600	5080315

Tele Defender

Combined protection device for VDSL, ISDN and DSL systems




- Low protection level at a high current load
- "Push-in" clamps for quick installation
- Bandwidth-optimised for secure transmission up to 225 MHz
- Surface mounting

The data cable protection devices for telecommunications applications are available as combination protection and fine protection. Depending on the application, from DSL through to analogue communication, the devices are used for direct intermediate switching into the data cable, meaning that

they can easily be retrofitted in existing installations. The devices differ in their connection technology and transmission cable and are thus optimised for their appropriate applications, in order to cause the lowest attenuation level possible.



Combination protection device TD-4/I for ISDN and DSL systems




Data cable protection device for telecommunications equipment

- Low protection level at a high current load
 - "Push-in" terminals for quick installation
 - Bandwidth-optimised for secure transmission
 - Surface mounting
 - Visual function display
- Application: DSL systems, IP connections, ISDN or analogue telecommunications

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TD-4/I	120	170	4	Terminal	1	11.000	5081690

Connection options




TD-4/I	
Maximum continuous voltage AC	U_c 120 V
Maximum continuous voltage DC	U_c 170 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	4
Rated current	I_L 0.2 A
Capacity (wire-wire)	<50 pF
Capacity (wire-earth)	<10 pF
Series resistance per wire	9 Ω ± 10 %
Impulse durability wire-wire	C2: 18 kV / 9 kA (8/20μs)
Impulse durability wire-earth	C2: 18 kV / 9 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	25 kA
Total discharge current (10/350)	D1: 12,5 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<650 V
Protection level, shield-earth (S-PE)	850 V
Frequency range	0 - 100 MHz
Insertion loss	S_{21} ≤3 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Surface-mounted
Connection system	Terminal
Protection rating	IP54
Shielding connection available	Yes
Connection cross-section, flexible	0.14 - 0.75 mm ²
Connection cross-section, multi-wire	0.14 - 0.75 mm ²
Connection cross-section, rigid	0.14 - 0.75 mm ²
Testing standard	IEC 61643-21

Schutzinstallationen Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25

Surge protection

Combination protection device TD-2d-V for VDSL systems



Surge protection

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TD-2D-V	125	180	2	Terminal	1	9.500	5081698


Data cable protection device for telecommunications equipment

- Low protection level at a high current load
- "Push-in" clamps for quick installation
- Bandwidth-optimised for secure transmission up to 225 MHz
- Surface mounting

Application: Ideal for all DSL systems, IP connections, ISDN or analogue telecommunications


TD-2D-V	
Maximum continuous voltage AC	U_c 125 V
Maximum continuous voltage DC	U_c 180 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_L 0.5 A
Capacity (wire-wire)	<10 pF
Capacity (wire-earth)	<20 pF
Series resistance per wire	2,2 $\Omega \pm 5\%$
Impulse durability wire-wire	C2: 15 kV / 7,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 15 kV / 7,5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	22,5 kA
Total discharge current (10/350)	D1: 7,5 kA
Protection level wire-wire	<350 V
Protection level wire-earth	<600 V
Frequency range	0 - 225 MHz
Insertion loss	S_{21} ≤ 3 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Surface-mounted
Connection system	Terminal
Protection rating	IP54
Shielding connection available	Yes
Connection cross-section, flexible	0.14 - 1 mm ²
Connection cross-section, multi-wire	0.14 - 1 mm ²
Connection cross-section, rigid	0.08 - 1.5 mm ²
Testing standard	IEC 61643-21

Connection options





Combination protection device TD-2/D-HS for ISDN and DSL systems




Data cable protection devices for telecommunication systems

- Low protection level at high current load
- Screwless terminals or connectable
- Bandwidth-optimised for secure transmission
- Quick mounting onto DIN rail for a telephone line
- Visual function display

Application: DSL systems, ISDN or analogue telecommunication

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TD-2/D-HS	120	170	2	Terminal	1	4.800	5081694

Connection options



TD-2/D-HS	
Maximum continuous voltage AC	U_c 120 V
Maximum continuous voltage DC	U_c 170 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	2
Rated current	I_L 0.2 A
Capacity (wire-wire)	<50 pF
Capacity (wire-earth)	<50 pF
Series resistance per wire	9 Ω \pm 10 %
Impulse durability wire-wire	C2: 18 kV / 9 kA (8/20 μ s)
Impulse durability wire-earth	C2: 18 kV / 9 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	D1: 5 kA kA
Protection level wire-wire	<300 V
Protection level wire-earth	<650 V
Frequency range	0 - 75 MHz
Insertion loss	S_{21} \leq 3 dB
Temperature range	ϑ -40 - +80 °C
Installation type	DIN rail 35 mm
Connection system	Terminal
Protection rating	IP20
Shielding connection available	No
Connection cross-section, flexible	0.14 - 2.5 mm ²
Connection cross-section, multi-wire	0.14 - 2.5 mm ²
Connection cross-section, rigid	0.14 - 2.5 mm ²
Testing standard	IEC 61643-21



Tele Defender

Combination and fine protection devices RJ11-Tele and RJ45 Tele for analogue cables




- In aluminium housing
- With two-stage protection circuit
- Simple mounting
- Inc. 150 mm connecting cable with RJ 11 and/or RJ 45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting

The data cable protection devices for telecommunications applications are available as combination protection and fine protection. Depending on the application, from DSL through to analogue communication, the devices are used for direct intermediate switching into the data cable, meaning that

they can easily be retrofitted in existing installations. The devices differ in their connection technology and transmission cable and are thus optimised for their appropriate applications, in order to cause the lowest attenuation level possible.



Fine protection device TELE 4-F for ISDN RJ11




Data line protection device for analogue telecommunications systems

- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems

Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ11-TELE 4-F	Fine protection, 4 wires	RJ11	1	14.000	5081977


Connection options



RJ11-TELE 4-F	
Maximum continuous voltage AC	U_c 120 V
Maximum continuous voltage DC	U_c 170 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Number of poles	4
Series resistance per wire	$2,2 \Omega \pm 10 \%$
Total discharge current (8/20)	4 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Protection level, wire-earth at 1 kV/ μ s (C3)	U_p <245 V
Frequency range	0 - 18 MHz
Insertion loss	S_{21} ≤ 3 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	RJ11
Protection rating	IP40
Earthing via:	Connection cable
Testing standard	IEC 61643-21



Combination protection device TELE 4-C for ISDN RJ11



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
RJ11-TELE 4-C	Combi protection, 4 wires	RJ11	1	14.000	5081975


Data line protection device for analogue telecommunications systems

- In aluminium housing
- With 2-stage protection circuit
- Simple mounting
- Incl. 150 mm connection cable with RJ11 and/or RJ45 connectors
- Optimised bandwidth for TC systems
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: For analogue telecommunication systems

RJ11-TELE 4-C	
Maximum continuous voltage AC	U_c 120 V
Maximum continuous voltage DC	U_c 170 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0-3
Number of poles	4
Series resistance per wire	$8,2 \Omega \pm 10 \%$
Total discharge current (8/20)	4 kA
Total discharge current (10/350)	1,5 kA
Protection level wire-wire	<300 V
Protection level wire-earth	<600 V
Protection level, wire-earth at 1 kV/ μ s (C3)	U_p <245 V
Frequency range	0 - 12 MHz
Insertion loss	S_{21} ≤ 3 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	RJ11
Protection rating	IP40
Earthing via:	Connection cable
Testing standard	IEC 61643-21


Connection options



LSA-Plus technology

Basic and fine protection

Surge protective devices for industrial telecommunications applications





- Simple installation
- Protection up to ten two-core wires
- Low protection level
- High arresting capacity
- High broadband in basic protection
- Wide range of uses

In particular with multi-wire cable systems, such as telecommunications distribution systems, the LSA surge voltage components offer rapid, adequate protection. The LSA system offers both basic protection modules and fine protection modules to

protect up to ten two-core wires per connection strip. These are split up into separating and connection strips and must be selected according to the application.



LSA basic protection magazine






Type	Installation type	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
LSA-B-MAG	LSA-Plus, connectable	20	1	8.600	5084020

LSA basic protection magazine for use in multi-core data cable systems, MCR systems and telephone switchboards.

- Basic protection
- Equipped with 20 gas arresters
- Max. voltage: 180 V

Application: Directly on LSA-Plus separating strips or connection rails (e.g. OBO LSA-A-LEI (5084 00 8) or OBO LSA-T-LEI (5084 01 2)).

Combination protection device LSA BF 180



Type	Installation type	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
LSA-BF-180	LSA-Plus, connectable	2	1	0.500	5084024



LSA basic and fine protection, for application in MCR systems

- Basic and fine protection
- Coarse protection using fail-safe technology.
- With PTC protection components against overcurrent.
- Max. voltage: 180 V

Application: Directly on LSA-Plus separating strip or connection rails with earthing rail (e.g. OBO LSA-A-LEI (5084 00 8) or OBO LSA-T-LEI (5084 01 2), and OBO LSA-E (5084 03 2))



LSA connection strip





LSA connection strip 2/10 for attaching 10 double-cores.

- For use with protection element LSA-B-MAG
- Fastening to mounting trough LSA-M
- Colour: Grey
- Clampable cross-sections 0.14–0.5 (AWG 26-20)

Type	Colour	Pack Piece	Weight kg/100 pc.	Item no.
LSA-A-LEI	Grey	1	5.100	5084008



LSA separating strip





LSA separating strip 2/10 for attaching up to 10 double-cores.

- For use with protection element LSA-BF-180; LSA-BF-24; LSA-B-MAG
- Fastening to mounting trough LSA-M
- Colour: White
- Clampable cross-sections 0.14–0.5 mm2 (AWG 26-20)

Type	Colour	Pack Piece	Weight kg/100 pc.	Item no.
LSA-T-LEI	White	1	5.400	5084012



LSA earthing strip




Type	Colour	Pack Piece	Weight kg/100 pc.	Item no.
LSA-E-LEI	Red	1	6.500	5084016

LSA earthing strip, 40-pole for connecting earthing cables or screens to the earth connection.

- Complete with connection line, green-yellow, 1.5 mm²
- Colour: Red

LSA simple tool





Type	Pack Piece	Weight kg/100 pc.	Item no.
LSA-TOOL	1	0.600	5084040

Simple tool for the soldering, bolting and stripping-free connection of cores, without cutter.





LSA earthing rail





Earth rail as earth connection between surge protectors LFS-BF... (1 DA) and distributor connector LSA-...-LEI.

Type	Pack Piece	Weight kg/100 pc.	Item no.
LSA-E	1	1.275	5084032

St



LSA installation trough




Installation trough for 5 connection rails or separating strips. Grid 22.5 mm.
Depth: 22 mm; 30 mm; 50 mm

Type	Pack Piece	Weight kg/100 pc.	Item no.
LSA-M	1	7.800	5084036



LSA protective housing



Type	Colour	Pack Piece	Weight kg/100 pc.	Item no.
LSA-G	Light grey	1	57.500	5084048

- Protective housing for an LSA 10 DA bar
- Protective housing for 10 wire pairs
 - Housing can be locked
 - Incl. key
 - 4x cable fixing
 - Light grey

Surge protection

Net Defender

Surge protection for data and network technology
PoE++ or 4PPoE Standard (IEEE 802.3bt)




- Connectable protection device
- High-performance surge protection
- Usable in the "Channel Link" up to 10 GBit
- Supports Power over Ethernet to 1 A
- Testing protocol available

The "Net Defender" permits the use of Power over Ethernet with nominal currents of up to 1 A and optimised surge protection in the channel up to 10 GBit/s. This corresponds to a Channel Performance according to ISO/IEC 11801 Amd. 2 of Class EA or CAT 6A to TIA/ANSI. Of course,

reverse compatibility is also guaranteed. To ensure easy installation, the "Net Defender" can be snapped directly onto the DIN rail and uses it to create the necessary equipotential bonding. Alternatively, terminal protection using a separately connectable earthing line is possible.



Surge protection for high-speed networks up to 10 GBit (Class EA/CAT6A)



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6A/EA	Fine protection, 8 wires + shield	RJ45 8(8)	1	16.600	5081800


Data cable protection device for high-speed networks

- Protection class: Fine protection
- High-quality RJ45 sockets
- Low protection level at high current load
- Earthing via DIN rail or connection cable
- Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
- Tested transmission quality in networks up to 10 GBit/s (Class EA) or CAT6
- Rapid installation through plug-in version
- Incl. DIN rail fastening set and earthing cable

Application example: 10 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces

ND-CAT6A/EA	
Maximum continuous voltage AC U_c	41 V
Maximum continuous voltage DC U_c	58 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Channel performance ISO/IEC	Class EA
Channel performance Ansi/EA	CAT 6A
Number of poles	8
Rated current I_L	1 A
Impulse durability wire-wire	C1: 0,3 kV / 0,15 kA (8/20 μ s)
Impulse durability wire-earth	C2: 2 kV / 1 kA (8/20 μ s)
Total discharge current (8/20)	7 kA
Protection level wire-wire	<120 V
Protection level wire-earth	<700 V
Frequency range	>500 MHz
Temperature range ϑ	-40 - +80 °C
Installation type	Connector/cable adapter
Connection system	RJ45 8(8)
Protection rating	IP10
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable / DIN rail
Testing standard	IEC 61643-21


Connection options



Alu



Surge protection for high-speed networks up to 1 GBit (Class ND-CAT6/E-F)




- Data cable protection device for high-speed networks
- High-quality RJ45 sockets
 - Low protection level at high current load
 - Earthing via DIN rail or connection cable
 - Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
 - Tested transmission quality in networks up to 1 GBit/s (Class E) or CAT6
 - Fast installation through plug-in version
 - Incl. DIN rail fastening set and earthing cable

Application example: 1 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces

Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6/E-F	Fine protection, 8 wires + shield	RJ45 8(8)	1	16.380	5081802

Connection options




ND-CAT6/E-F	
Maximum continuous voltage AC	U_c 41 V
Maximum continuous voltage DC	U_c 58 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Channel performance ISO/IEC	Class E
Channel performance Ansi/EA	CAT 6
Number of poles	8
Rated current	I_L 1 A
Impulse durability wire-wire	C1: 0,3 kV / 0,15 kA (8/20 μ s)
Impulse durability wire-earth	C2: 3 kV / 1,5 kA (8/20 μ s)
Total discharge current (8/20)	5 kA
Protection level wire-wire	<40 V
Protection level wire-earth	<900 V
Frequency range	>250 MHz
Temperature range	ϑ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	RJ45 8(8)
Protection rating	IP10
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable / DIN rail
Testing standard	IEC 61643-21

Schutzinstallationen: Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25

Surge protection



Surge protection for high-speed networks up to 1 GBit (Class ND-CAT6/E-B)



Surge protection


Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
ND-CAT6/E-B	Basic protection, 8 wires + shield	RJ45 8(8)	1	16.220	5081804

- Data cable protection device for high-speed networks
- Protection class: Basic protection
 - High-quality RJ45 sockets
 - Low protection level at high current load
 - Earthing via DIN rail or connection cable
 - Support of Power over Ethernet ++ (PoE++/4PPoE) to 1 A in accordance with IEEE 802.3
 - Tested transmission quality in networks up to 1 GBit/s (Class E) or CAT6
 - Rapid installation through plug-in version
 - Incl. DIN rail fastening set and earthing cable

Application example: 1 GBit Ethernet, 10/100 MBit Ethernet, PoE applications, IP camera systems, ISDN S0 interfaces


ND-CAT6/E-B	
Maximum continuous voltage AC U_c	46 V
Maximum continuous voltage DC U_c	65 V
Category	Type 1 / D1
Lightning protection zone LPZ	0→1
Channel performance ISO/IEC	Class E
Channel performance Ansi/EA	CAT 6
Number of poles	8
Rated current I_L	1 A
Impulse durability wire-wire	C2: 3 kV / 1,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 3 kV / 1,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<1100 V
Protection level wire-earth	<900 V
Frequency range	>250 MHz
Temperature range ϑ	-40 - +80 °C
Installation type	Connector/cable adapter
Connection system	RJ45 8(8)
Protection rating	IP10
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable / DIN rail
Testing standard	IEC 61643-21

Connection options





Combination arrester for 10Base2-/10Base5 networks




Data line protection device for coaxial Ethernet network systems

- In aluminium housing
- BNC connector m/f
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protecting video signals; cameras and/or CCTV units, Cheapernet, 10BASE2, 10BASE5

Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 MF-C	Combi protection	BNC	1	10.300	5082430


Connection options



KOAX B-E2 MF-C	
Maximum continuous voltage AC	U_c 4.2 V
Maximum continuous voltage DC	U_c 6.2 V
Category	Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ	0→3
Number of poles	1
Rated current	I_L 0.3 A
Series resistance per wire	4,7 Ω \pm 10%
Wave resistance	Z_L 75 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 1 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	2 kA
Protection level wire-wire	<75 V
Protection level wire-earth	<600 V
Frequency range	0 - 68 MHz
Insertion loss	S_{21} \leq 1,7 dB
Return loss	S_{11} \geq 14 dB
Temperature range	ϑ -20 - +80 °C
Installation type	Connector/cable adapter
Connection system	BNC
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable
Testing standard	IEC 61643-21



Fine protection for 10Base2-/10Base5 networks



Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 MF-F	Fine protection	BNC	1	9.800	5082432

Data line protection device for coaxial Ethernet network systems


- In aluminium housing
- BNC connector m/f
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protecting video signals; cameras and/or CCTV units, Cheapernet, 10BASE2, 10BASE5

KOAX B-E2 MF-F


Maximum continuous voltage AC	U_c	4.2 V
Maximum continuous voltage DC	U_c	6.2 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1-3
Number of poles		1
Rated current	I_L	1 A
Wave resistance	Z_L	75 Ω
Impulse durability wire-wire		C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Protection level wire-wire		<40 V
Protection level wire-earth		<600 V
Frequency range		0 - 70 MHz
Insertion loss	S_{21}	≤ 1 dB
Return loss	S_{11}	≥ 14 dB
Temperature range	ϑ	-20 - +80 $^{\circ}$ C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options





Data cable protection device for coaxial TV / camera systems




Data cable protection device for coaxial TV / camera systems

- In aluminium housing
- BNC connector socket/socket
- Simple mounting with adapter plug
- Two-stage protection circuit
- DIN rail mounting with DLS-BS accessories (5082 38 2)

Application: Protection of CCTV, video signals; cameras and/or TV systems

Type	Version	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
KOAX B-E2 FF-F	Fine protection	BNC	1	14.400	5082434

Connection options




KOAX B-E2 FF-F	
Maximum continuous voltage AC	U_c 4.2 V
Maximum continuous voltage DC	U_c 6.2 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	1
Rated current	I_L 1 A
Wave resistance	Z_L 75 Ω
Impulse durability wire-wire	C1: 1 kV / 0,5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<40 V
Protection level wire-earth	<600 V
Frequency range	0 - 160 MHz
Insertion loss	S_{21} \leq 1,7 dB
Return loss	S_{11} \geq 14 dB
Temperature range	ϑ -20 - +80 °C
Installation type	Connector/cable adapter
Connection system	BNC
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Earthing via:	Connection cable
Testing standard	IEC 61643-21

Schutzinstallationen: Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25

Surge protection

Fastening set for DIN profile rail



Version		Pack Piece	Weight kg/100 pc.	Item no.
Type				
DLS-BS	For mounting: <ul style="list-style-type: none"> • Coax B-E2/... • Coax N-E5/... • RJ 11-Tele/4... • RJ45 S... 	1	5.000	5082382


DLS-BS: The fastening set is designed for a DIN rail and wall mounting and can be used for the data cable protection devices listed below:

- Coax N-E5/...
- Coax B-E2/...
- RJ 11-Tele/4...
- RJ 45 S-...





Combined protection device 2in1 for CCTV camera systems





Combination protection device for IP-based TV/camera systems

- Protection of power and data interface in a single device
- In aluminium housing
- Simple mounting with adapter plug
- Two-stage protection circuit
- Three-pole power connection for the power interface
- RJ45 connection for the data interface
- With LED operation display (OS)
- Incl. DIN rail fastening set

Application: Protection of CCTV, video signals, (IP) cameras and/or TV systems

Type	Maximum continuous voltage (L-N) V	Maximum discharge current (8/20 μs) kA	Pack Piece	Weight kg/100 pc.	Item no.
PND-2in1-C-OS	255	10	1	27.000	5081070


Connection options



PND-2in1-C-OS	
Temperature range	θ -20 - +80 °C
Installation type	Installation
Protection rating	IP20
Earthing via:	Connection cable / DIN rail
Lightning protection zone LPZ	1→3
Power	
SPD to IEC 61643-11	Class II+III
SPD to EN 61643-11	Type 2+3
Maximum continuous voltage (L-N)	U_c 255 V
Rated current	I_L 16 A
Protection level	U_o <1,3 kV
Idle voltage	U_{oc} 10 kV
Nominal discharge current (8/20 μs)	$I_n / L-N$ 5 kA
Maximum discharge current (8/20 μs)	I_{max} 10 kA
Network	
Maximum continuous voltage AC	U_c 5.65 V
Maximum continuous voltage DC	U_c 8 V
Category	Type 1+2+3 / D1+C2+C1
Impulse durability wire-wire	C1: 0,3 kV / 0,15 kA (8/20μs)
Impulse durability wire-earth	C2: 3 kV / 1,5 kA (8/20μs)
Protection level wire-wire	<40 V
Protection level wire-earth	<450 V
Frequency range	0 - 100 MHz
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21



Combined protection device 3in1 for CCTV camera systems



Type	Maximum continuous voltage (L-N) V	Maximum discharge current (8/20 μs) kA	Pack Piece	Weight kg/100 pc.	Item no.
PND-3in1-C-OS	255	10	1	29.900	5081072



Combination protection device for coaxial TV/camera systems


- Protection of power and data interfaces in a single device
- In aluminium housing
- Simple mounting with adapter
- Two-stage protection circuit
- Three-pole power connection for the power interface
- With LED operation display (OS)
- Incl. DIN rail fastening set

Application: Protection of CCTV, video signals, cameras and/or TV systems

PND-3in1-C-OS	
Lightning protection zone LPZ	1-3
Earthing via:	Connection cable / DIN rail
Protection rating	IP20
Power	
SPD to IEC 61643-11	Class II+III
SPD to EN 61643-11	Type 2+3
Maximum continuous voltage (L-N)	U_c 255 V
Rated current	I_L 16 A
Protection level	U_p <1,3 kV
Nominal discharge current (8/20 μs)	$I_n / L-N$ 5 kA
Maximum discharge current (8/20 μs)	I_{max} 10 kA
Data	
Maximum continuous voltage AC	U_c 5.65 V
Maximum continuous voltage DC	U_c 8 V
SPD to IEC 61643-21	Class I+II / D1+C2
Category	Type 1+2 / D1+C2
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Impulse current (10/350)	I_{imp} 1 kA
Protection level wire-earth	<450 V
Protection level wire-wire	<65 V
Frequency range	0-100 MHz
Video	
Maximum continuous voltage AC	U_c 5.65 V
Maximum continuous voltage DC	U_c 8 V
SPD to IEC 61643-21	Class I+II / D1+C2
Category	Type 1+2 / D1+C2
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse current (10/350)	I_{imp} 1 kA
Protection level wire-wire	<90 V
Protection level wire-earth	<150 V
Frequency range	0-100 MHz
Screen connection	Yes
Screening	Direct
Temperature range	θ -20 - +80 °C

Connection options





DS family

Coaxial protection devices for S-UHF, BNC, N, TNC, F and SMA connection



Surge protection




- Coaxial protection devices
- Optimum protection for sensitive systems
- Low insertion attenuation and low return loss at different wave resistances
- High bandwidth

The coaxial protection devices of type DS offer optimum protection of sensitive systems, based on coaxial plug connections. The low insertion attenuation and low return attenuation at different wave resistances offer ideal protection for any application. In accordance with their structure, the protec-

tion devices are switched into the application in series, and are connected to the local equipotential bonding. The direct shield earthing avoids reducing of the shield performance.



Coaxial protection devices for S-UHF connection: male/female




Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μ s)
- Simple installation (adapter plug), m = male/f = female connector
- Various plug combinations
- With UHF connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
S-UHF M/W	UHF	0 - 1,3 GHz	1	7.000	5093023



Connection options



S-UHF M/W	
Maximum continuous voltage AC	U_c 130 V
Maximum continuous voltage DC	U_c 185 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0-2
Number of poles	1
Rated current	I_L 10 A
Wave resistance	Z_L 50 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	5 kA
Protection level	<800 V
Frequency range	0 - 1,3 GHz
Insertion loss	S_{21} \leq 0,2 dB
Return loss	S_{11} \geq 14 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	UHF
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21



Coaxial protection devices for S-UHF connection: female/female



Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
S-UHF W/W	UHF	0-1,3 GHz	1	7.000	5093015


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μs)
- Simple installation (adapter plug), m = male/f = female connector
- Various plug combinations
- With UHF connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

S-UHF W/W


Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 1,3 GHz
Insertion loss	S_{21}	≤0,2 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		UHF
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options





Coaxial protection device for BNC connection: male/female




Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μ s)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-BNC M/W	BNC	0 - 2,2 GHz	1	6.500	5093252

Connection options




DS-BNC M/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 2,2 GHz
Insertion loss	S_{21}	$\leq 0,95$ dB
Return loss	S_{11}	≥ 14 dB
Temperature range	ϑ	-40 - +80 $^{\circ}$ C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Coaxial protection device for BNC connection: female/female



Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-BNC W/W	BNC	0-2,2 GHz	1	6.000	5093236


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

DS-BNC W/W


Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 2,2 GHz
Insertion loss	S_{21}	≤0,95 dB
Return loss	S_{11}	≥14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		BNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options





Coaxial protection device for BNC connection: male/male




Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μ s)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With BNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Type	Con- tion system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-BNC M/M	BNC	0-2,2 GHz	1	7.000	5093260


Connection options



DS-BNC M/M	
Maximum continuous voltage AC	U_c 130 V
Maximum continuous voltage DC	U_c 185 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0-2
Number of poles	1
Rated current	I_L 10 A
Wave resistance	Z_L 50 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	5 kA
Protection level	<800 V
Frequency range	0 - 2,2 GHz
Insertion loss	S_{21} \leq 0,95 dB
Return loss	S_{11} \geq 14 dB
Temperature range	ϑ -40 - +80 $^{\circ}$ C
Installation type	Connector/cable adapter
Connection system	BNC
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21



Coaxial protection device for N connection: male/female




Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N M/W	N	0-3 GHz	1	12.200	5093996

- Coaxial data cable protection devices
- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
 - Simple mounting (adapter plug), m = plug/f = female connector
 - Optimised transmission behaviour
 - 5-year guarantee
 - With N connector
 - Including OBO M25 Quick clip for simple installation


DS-N M/W	
Maximum continuous voltage AC	U_c 130 V
Maximum continuous voltage DC	U_c 185 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0-2
Number of poles	1
Rated current	I_L 10 A
Wave resistance	Z_L 50 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	5 kA
Protection level	<800 V
Frequency range	0 - 3 GHz
Insertion loss	S_{21} \leq 0,62 dB
Return loss	S_{11} \geq 14 dB
Temperature range	ϑ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	N
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21

Connection options





Coaxial protection device for N connection: female/female




Coaxial data cable protection devices

- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter plug), m = plug/f = female connector
- Optimised transmission behaviour
- 5-year guarantee
- With N connector
- Including OBO M25 Quick clip for simple installation

Type	Con- nection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N W/W	N	0-3 GHz	1	11.500	5093988

Connection options




DS-N W/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3 GHz
Insertion loss	S_{21}	$\leq 0,62$ dB
Return loss	S_{11}	≥ 14 dB
Temperature range	θ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		N
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Coaxial protection device for N connection up to 6 GHz: male/female



Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-N-6 M/W	N	0-6 GHz	1	7.830	5093998


Coaxial data cable protection devices for transmission and reception technology

- With N-Connector, male/female
- High impulse current load capacity: 2.5 kA (10/350)
- Simple mounting (adapter), m = connector, w = socket
- Low protection level at high current loads
- Optimum transmission behaviour:
 - Low reflection behaviour
 - Bandwidth-optimised for secure transmission up to 6 GHz
- Available in 50 Ω technology

Application: For example: SAT-TV C band, WIMAX, WLAN applications, DVB-T2


DS-N-6 M/W	
Maximum continuous voltage AC	U_c 50 V
Maximum continuous voltage DC	U_c 70 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0-2
Number of poles	1
Rated current	I_L 10 A
Wave resistance	Z_L 50 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp} 2.5 kA
Protection level	<750 V
Frequency range	0 - 6 GHz
Insertion loss	S_{21} ≤0,1 dB
Return loss	S_{11} ≥22 dB
Temperature range	θ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	N
Protection rating	IP65/67
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21

Connection options





Coaxial protection device for TNC connection: male/female




Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μ s)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With TNC connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-TNC M/W	TNC	0-4 GHz	1	7.953	5093270

Connection options





DS-TNC M/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 4 GHz
Insertion loss	S_{21}	$\leq 0,5$ dB
Return loss	S_{11}	≥ 14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		TNC
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Coaxial protection device for 7/16 connection: male/female



Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-7 16 M/W	7/16	0-3GHz	1	35.500	5093171

Coaxial data protection device


- Basic protection
- Simple mounting (adapter)
- Optimum transmission
- High pulse load capacity
- With 7/16 connector

Application: to protect mobile telephony applications.

DS-7 16 M/W


Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3 GHz
Insertion loss	S_{21}	$\leq 0,95$ dB
Return loss	S_{11}	≥ 14 dB
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		7/16
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21

Connection options





Coaxial protection device for F connection: male/female




Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μ s)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With F connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T(2)

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-F MW	F	0-3,4 GHz	1	9.000	5093275

Connection options




DS-F MW

Maximum continuous voltage AC	U_C	130 V
Maximum continuous voltage DC	U_C	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current	I_L	5 A
Wave resistance	Z_L	75 Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	1 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		2 kA
Protection level		<800 V
Frequency range		0 - 3,4 GHz
Insertion loss	S_{21}	$\leq 0,9$ dB
Return loss	S_{11}	≥ 14 dB
Temperature range	ϑ	-40 - +80 $^{\circ}$ C
Installation type		Connector/cable adapter
Connection system		F
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Coaxial protection device for F connection: fe-male/female



Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-F W/W	F	0-3,4 GHz	1	9.000	5093272


Coaxial data cable protection devices

- Basic protection
- High pulsed current carrying capacity 2 x 2.5 kA (10/350 μs)
- Simple installation (adapter plug), m = plug/f = female connector
- Various plug combinations
- With F connector
- Optimised transmission behaviour
- Including OBO M25 Quick clip for simple installation

Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T(2)



DS-F W/W	
Maximum continuous voltage AC	U_c 130 V
Maximum continuous voltage DC	U_c 185 V
Category	Type 1+2 / D1+C2
Lightning protection zone LPZ	0→2
Number of poles	1
Rated current	I_L 5 A
Wave resistance	Z_L 75 Ω
Impulse durability wire-wire	C2: 10 kV / 5 kA (8/20μs)
Impulse durability wire-earth	C2: 10 kV / 5 kA (8/20μs)
Impulse discharge current (10/350)	I_{imp} 1 kA
Total discharge current (8/20)	10 kA
Total discharge current (10/350)	2 kA
Protection level	<800 V
Frequency range	0 - 3,4 GHz
Insertion loss	S_{21} ≤0,9 dB
Return loss	S_{11} ≥14 dB
Temperature range	θ -40 - +80 °C
Installation type	Connector/cable adapter
Connection system	F
Protection rating	IP40
Shielding connection available	Yes
Shield connection	Direct
Testing standard	IEC 61643-21

Connection options





Coaxial protection device for SMA connection: female/female




Coaxial data cable protection devices

- High pulse current carrying capacity $2 \times 2.5 \text{ kA}$ (10/350)
- Simple mounting (adapter connector), m = connector, f = socket
- Optimised transmission behaviour
- 5-year guarantee
- With SMA connector
- Including OBO Multi-Quick clip 25-28 for simple installation
- 50Ω technology

Application: Radio and data technology with SMA connector

Type	Connection system	Frequency range	Pack Piece	Weight kg/100 pc.	Item no.
DS-SMA W/W	SMA	0-3,7 GHz	1	7.500	5093277

Connection options




DS-SMA W/W

Maximum continuous voltage AC	U_c	130 V
Maximum continuous voltage DC	U_c	185 V
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0→2
Number of poles		1
Rated current	I_L	10 A
Wave resistance	Z_L	50Ω
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350)	I_{imp}	2.5 kA
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		5 kA
Protection level		<800 V
Frequency range		0 - 3,7 GHz
Insertion loss	S_{21}	$\leq 0,2 \text{ dB}$
Return loss	S_{11}	$\geq 14 \text{ dB}$
Temperature range	ϑ	-40 - +80 °C
Installation type		Connector/cable adapter
Connection system		SMA
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21



Coaxial protection device for SAT and cable multi-switch



Type	Connection system	Frequency range	Connection system	Pack Piece	Weight kg/100 pc.	Item no.
TV 4+1	F	0,5-2,8 GHz	F	1	37.000	5083400


Coaxial data line protection for TV reception systems


- Protects up to four SAT lines
- Protects one terrestrial line, e.g. DVB-T.
- Simple mounting using screws and holder
- With F-connector
- Optimum transmission behaviour with 75 Ohm technology.

Application: Protection of TV and SAT systems, multi-switches, receivers and DVB-T receivers

TV 4+1		
Maximum continuous voltage Vc SAT inputs	U_C	22 V
Maximum continuous voltage Vc terrestrial input	U_C	70 V
Category		Type 2+3 / C2+C1
Lightning protection zone LPZ		1-3
Number of poles		5
Rated current	I_L	2 A
Wave resistance	Z_L	75 Ω
Nominal discharge current SAT inputs	I_n	300 A
Lightning impulse current terrestrial input	I_{imp}	1 kA
Protection level SAT inputs at In	U_d	<45 V
Protection level Terrestrial input at In		<500 V
Frequency range		0,5 - 2,8 GHz
Insertion loss	S_{21}	≤ 3 dB
Return loss	S_{11}	> 30 dB
Temperature range	θ	-40 - +80 °C
Installation type		Surface-mounted
Connection system		F
Protection rating		IP10
Shielding connection available		Yes
Shield connection		Direct
Earthing via:		Connection cable
Testing standard		IEC 61643-21

Connection options





Surge protective devices for photovoltaic applications

Type 1+2 and type 2 for 1,000 V and 1,500 V DC



Surge protection



- Surge protection according to EN/IEC 60364-7-712 (VDE 0100-712)
- Error-resistant Y circuit with status display
- The FS variant has a potential-free changeover contact for remote signalling




Type 1+2 1000 V



Type 2 1500 V



PV complete block 1500 V DC




Type 1+2 combination arrester for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protective devices for PV systems.

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1500	1500	Y configuration	1	49.200	5094240


Connection options



V-PV-T1+2-1500	
U max DC	U _c DC 1500 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Impulse discharge current (10/350)	I _{imp} 6.25 kA
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,5 kV
Response time	t _A < 25 ns
Temperature range	θ -40 - 80 °C
Protection rating	IP20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 35 mm ²



PV complete block 1500 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1500FS	1500	Y configuration + RS	1	49.600	5094242


Type 1+2 combination arrester for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protective devices for PV systems.


V-PV-T1+2-1500FS	
U max DC	U _c DC 1500 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Impulse discharge current (10/350)	I _{imp} 6.25 kA
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,5 kV
Response time	t _A < 25 ns
Temperature range	θ -40 - 80 °C
Protection rating	IP20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 35 mm ²

Connection options





PV complete block 1,000 V DC




Type 1+2 combination arrester according to EN 50539-11 for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protective devices for PV systems.

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1000	1000	Y configuration	1	40.700	5094230


Connection options



V-PV-T1+2-1000		
U max DC	U _c DC	1000 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I _{imp}	6.25 kA
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 3,3 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²



PV complete block 1,000 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T1+2-1000FS	1000	Y configuration + RS	1	41.200	5094232


Type 1+2 combination arrester according to EN 50539-11 for lightning and surge protection of PV systems.

- Lightning protection equipotential bonding according to IEC 62305 (VDE 0185-305)
- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity to 12.5 kA (10/350) and 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Lightning current and surge protective devices for PV systems.


V-Type		V-PV-T1+2-1000FS	
U max DC		U _c DC	1000 V
SPD to EN 61643-11			Type 1+2
Lightning protection zone LPZ			0→2
Impulse discharge current (10/350)	I _{imp}		6.25 kA
Nominal discharge current (8/20)	I _n		20 kA
Maximum discharge current (8/20 μs)	I _{max}		40 kA
Protection level	U _p		< 3,3 kV
Response time	t _A		< 25 ns
Temperature range	θ		-40 - 80 °C
Protection rating			IP20
Division unit TE (17.5 mm)			4
Connection cross-section, rigid			2.5 - 35 mm ²
Connection cross-section, multi-wire			2.5 - 35 mm ²
Connection cross-section, flexible			2.5 - 35 mm ²

Connection options





PV combination arrester V25, 900 V DC




V25 combination arrester, type 1+2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 7 kA (10/350) and 50 kA (8/20) per pole
- Low DC protection level: < 3.0 kV and Voc max = 900 V DC
- With visual function display for use in distributor housings

Application: PV systems with lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V25-B+C 3-PH900	900	3-pole for PV systems	1	42.200	5097447


Connection options



V25-B+C 3-PH900	
U max DC	U _c DC 900 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Impulse discharge current (10/350)	I _{imp} 7 kA
Nominal discharge current (8/20)	I _n 30 kA
Maximum discharge current (8/20 μs)	I _{max} 50 kA
Protection level	U _p < 3,0 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	3
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²



PV combination arrester V25, 900 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V25-B+C 3PHFS900	900	3 pole for PV systems with RS	1	53.500	5097448

V25 combination arrester, type 1+2, for PV systems with FS contact as potential-free changeover


- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 7 kA (10/350) and 50 kA (8/20) per pole
- Low DC protection level: < 3.0 kV and Voc max. = 900 V DC
- With visual display for use in distributor housings

Application: PV systems with lightning protection system

V25-B+C 3PHFS900


U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _p	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²

Connection options





PV combination arrester V50, 600 V DC




V50 combination arrester, type 1+2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity up to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC protection level: < 2.6 kV and $V_{oc\ max} = 600\ V\ DC$
- With visual function display for use in distributor housings

Application: PV systems with lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V50-B+C 3-PH600	600	3-pole for PV systems	1	41.000	5093623

Connection options




V50-B+C 3-PH600

U max DC	U _c DC	600 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I _{imp}	12.5 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _p	< 2,6 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²



PV combination arrester V50, 600 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V50-B+C 3PHFS600	600	3-pole for PV systems with FS	1	49.600	5093625


V50 combination arrester, type 1+2, for PV systems with FS contact as potential-free changeover

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC voltage protection level: < 2.6 kV and Voc max. = 600 V DC
- With visual display for use in distributor housings

Application: PV systems with lightning protection system


V50-B+C 3PHFS600	
U max DC	U _c DC 600 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Impulse discharge current (10/350)	I _{imp} 12.5 kA
Nominal discharge current (8/20)	I _n 30 kA
Maximum discharge current (8/20 μs)	I _{max} 50 kA
Protection level	U _p < 2,6 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²

Connection options





PV complete block 1500 V DC




Type 2 surge protection for PV plants.

- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity of 20 kA per pole and up to 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Surge protective devices for PV systems.

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T2-1500	1500	Y configuration	1	33.800	5094210


Connection options



V-PV-T2-1500

U max DC	U _e DC	1500 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 4,5 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - 80 °C
Protection rating		IP20
Division unit TE (17.5 mm)		4
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 35 mm ²

PV complete block 1500 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V-PV-T2-1500+FS	1500	Y configuration + RS	1	34.400	5094212


Type 2 surge protection for PV plants.

- Surge protection according to IEC 60364-7-712 (VDE 0100-712)
- Arresting capacity of 20 kA per pole and up to 40 kA (8/20)
- Error-resistant Y circuit with status display
- The FS variant possesses a potential-free changeover contact for remote signalling

Application: Surge protective devices for PV systems.


V-PV-T2-1500+FS	
U max DC	U _c DC 1500 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,5 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - 80 °C
Protection rating	IP20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 35 mm ²

Connection options





PV surge protection V20, 1000 V DC




V20 surge arrester, type 2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- V20-C 3-PH-1000 tested to EN 50539-11 (VDE / KEMA)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 4.0 kV and Voc max = 1,000 V DC
- With visual status display for use in distributor housings

Application: PV systems with or without separate lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3-PH-1000	1000	3-pole for PV systems	1	34.520	5094608


Connection options



V20-C 3-PH-1000	
U max DC	U _c DC 1000 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,0 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	3
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²



PV surge protection V20, 1000 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3PHFS-1000	1000	3-pole for PV systems with FS	1	44.500	5094574


V20 surge arrester, type 2, for photovoltaic systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit to VDE 0100-712 (EN 50539-12)
- Surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- V20-C 3-PH-1000 tested to EN 50539-11 (VDE / KEMA)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 4.0 kV and Voc max = 1,000 V DC
- With visual status display for use in distributor housings

Application: PV systems with or without separate lightning protection system


V20-C 3PHFS-1000	
U max DC	U _c DC 1000 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1-2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,0 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²

Connection options





PV surge protection V20, 600 V DC




V20 surge arrester, type 2, for PV systems

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 2.6 kV (U_{oc} max = 600 V DC)
- Arrester, connectable with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings

Application: PV systems with or without separate lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3PH-600	600	3-pole for PV systems	1	33.500	5094605

Connection options




V20-C 3PH-600

U max DC	U _c DC	600 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 2,6 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		3
Connection cross-section, rigid		2.5 - 35 mm ²
Connection cross-section, multi-wire		2.5 - 35 mm ²
Connection cross-section, flexible		2.5 - 25 mm ²



PV surge protection V20, 600 V DC with remote signalling



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 3PHFS-600	600	3-pole for PV systems; Y circuit with FS	1	41.500	5094576


V20 surge arrester, type 2, for PV systems with FS contact as potential-free changeover

- Complete unit, consisting of plug-in varistor arrester with cut-off unit
- Error-resistant Y circuit for use according to VDE 0100-712 (EN 50539-12)
- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC protection level: < 2.6 kV (Voc max = 600 V DC)
- Arrester, connectable with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings

Application: PV systems with or without separate lightning protection system


V20-C 3PHFS-600	
U max DC	U _c DC 600 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 2,6 kV
Response time	t _A < 25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	4
Connection cross-section, rigid	2.5 - 35 mm ²
Connection cross-section, multi-wire	2.5 - 35 mm ²
Connection cross-section, flexible	2.5 - 25 mm ²

Connection options





PV system solution, type 1+2, for inverter with 1 MPP tracker, 900 V DC




System solution for photovoltaic inverter with 1 separate MPP tracker

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- For each protection device, there are 3 terminal points up to 16 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Low DC protection level: < 3.0 kV (U_{oc} max = 900 V DC with V25-B+C/0-450PV)
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for the use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V25-BC3-PH900	900	Type 1+2 in housing with terminals	1	93.000	5088591

Connection options




VG-V25-BC3-PH900

U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _p	< 3,0 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		1.5 - 16 mm ²
Connection cross-section, flexible		1.5 - 10 mm ²
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP66



PV system solution, type 2, for inverter with 1 MPP tracker, 1,000 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-V20-C3-PH1000	1000	Type 2 in housing with terminals	1	87.000	5088593


System solution for photovoltaic inverter with 1 separate MPP tracker

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- For each protection device, there are 3 terminal points up to 16 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Low DC protection level: < 4.0 kV (Uoc max = 1,000 V DC with V20-B/0-500PV)
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for the use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!



VG-V20-C3-PH1000	
U max DC	U _c DC 1000 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,0 kV
Response time	t _A < 25 ns
Connection cross-section, rigid	1.5 - 16 mm ²
Connection cross-section, flexible	1.5 - 10 mm ²
Temperature range	ϑ -40 - +80 °C
Protection rating	IP66

Connection options





PV system solution, type 1+2, for inverter with 2 MPP trackers, 900 V DC




System solution for photovoltaic inverter with 2 separate MPP trackers

- Varistor arrester, connectable with disconnecting device in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (U_{oc} max = 1,000 V DC with V20-C/0-500PV)
- Low DC protection level: < 3.0 kV (U_{oc} max = 900 V DC with V25-B+C/0-450PV)
- Per protection device, there are 4 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for the use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!


Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BCPV900K 22	900	For two MPP and with terminal connection	1	220.000	5088566

Connection options



VG-BCPV900K 22	
U max DC	U_c DC 900 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Nominal discharge current (8/20)	I_n 30 kA
Maximum discharge current (8/20 μ s)	I_{max} 60 kA
Protection level	U_p < 3,0 kV
Response time	t_A < 25 ns
Temperature range	ϑ -30 - 90 °C
Protection rating	IP66

PV system solution, type 2, for inverter with 2 MPP trackers, 1,000 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-CPV1000K 22	1000	For two MPP and with terminal connection	1	216.600	5088568

System solution for photovoltaic inverter with 2 separate MPP trackers


- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Voc max = 1,000 V DC with V20-B+C/0-500PV)
- Per protection device, there are 4 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-CPV1000K 22



U max DC	U _c DC	1000 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 4,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP66

Connection options





PV system solution, type 1+2, for inverter with 3 MPP trackers, 900 V DC




System solution for photovoltaic inverter with 3 separate MPP trackers

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 01100-712 (50539-12)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Per protection device there are 6 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BCPV 900K 333	900	For three MPP and with terminal connection	1	546.000	5088579

Connection options




VG-BCPV 900K 333

U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	60 kA
Protection level	U _o	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP65



PV system solution, type 2, for inverter with 3 MPP trackers, 1,000 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-CPV 1000K 333	1000	For three MPP and with terminal connection	1	528.000	5088585

System solution for photovoltaic inverter with 3 separate MPP trackers


- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Voc max = 1,000 V DC with V20-B+C/0-500PV)
- Per protection device, there are 6 terminals up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-CPV 1000K 333


U max DC	U _c DC	1000 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 4,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP65

Connection options





Photovoltaic housing with connection terminals, unequipped




System solution for photovoltaic inverter with 3 separate MPP trackers, unequipped

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- 5088609: Two PV string inputs (MC4 plug connector) at an MPP inverter input, IN up to 15 A DC per MC4 connector
- 5088573: Per protection device there are 6 terminals up to 6 mm² pre-mounted in the housing, IN up to 30 A DC per terminal
- Unequipped, order upper parts separately
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BCPV U K 333	1000	For 3 MPPs, unequipped	1	478.000	5088573


Connection options



VG-BCPV U K 333

U max DC	U _c DC	1000 V
Connection cross-section, rigid		0.5 - 10 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	∅	-40 - +80 °C
Protection rating		IP65

Photovoltaic housing with 4 fuse holders, V25, 900 V



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC PV900KS4	900	Type 1+2 in housing with fuse holder (unequipped)	1	205.000	5088640

System solution for photovoltaic fuses (unequipped) for photovoltaic inverters with 1 MPP tracker


- Error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- (+) poles protected via 4 photovoltaic fuses 10 x 38 mm (unequipped), 900 V DC protected
- 4 (-) poles via terminal up to 6 mm² switched in parallel in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-BC PV900KS4


U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		1→2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	60 kA
Protection level	U _p	< 3,0 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		0.5 - 6 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	θ	-40 - +80 °C
Protection rating		IP 65

Connection options





Photovoltaic housing with 4 fuses 10 A




System solution for photovoltaic fuses for photovoltaic inverters with 1 MPP tracker

- Error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV ($V_{oc\ max} = 1,000\ V\ DC\ with\ V20-C/0-500PV$)
- (+) poles protected via 4 photovoltaic fuses 10x38 mm 10 A, 1,000 V DC protected
- 4 (-) poles via terminal up to 6 mm² switched in parallel in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems.
If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-C DCPH1000-4S	1000	Type 2 in housing with 4 PV fuses (10 A)	1	200.000	5088651

Connection options




VG-C DCPH1000-4S

U max DC	U _c DC	1000 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _b	< 4,0 kV
Response time	t _A	< 25 ns
Connection cross-section, rigid		0.5 - 6 mm ²
Connection cross-section, flexible		0.5 - 6 mm ²
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 65



Photovoltaic housing with 4 fuse holders, un-equipped



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-C PV1000KS4	1000	Type 2 in housing with fuse holder (unequipped)	1	190.000	5088654


System solution for photovoltaic fuses for photovoltaic inverters with 1 MPP tracker

- Error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 4.0 kV (Voc max = 1,000 V DC with V20-C/0-500PV)
- Item no.: 5088654: (+) poles protected via 4 photovoltaic fuses 10 x 38 mm (unequipped), 1,000 V DC protected
- Item no.: 5088640: (+) poles protected via 4 photovoltaic fuses 10 x 38 mm (unequipped), 900 V DC protected
- 4 (-) poles via terminal up to 6 mm² switched in parallel in the housing, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!


VG-C PV1000KS4	
U max DC	U _c DC 1000 V
SPD to EN 61643-11	Type 2
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,0 kV
Response time	t _A < 25 ns
Connection cross-section, rigid	0.5 - 6 mm ²
Connection cross-section, flexible	0.5 - 6 mm ²
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 65

Connection options





PV system solution, type 1+2, to 900 V DC with switch disconnecter (32 A)




- System solution for circuit breaker photovoltaic inverter with 1 MPP tracker
- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
 - Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
 - Circuit breaker (1,000 V; 32 A) for secure switch-off of the DC string cable
 - Per protection device there is 1 terminal up to 6 mm² pre-mounted in the housing, up to 30 A DC per terminal
 - Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside, including cable gland kit

For DC protection of the inverter in photovoltaic systems.
If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC DC-TS900	900	Type 1+2 and Benedikt LS32-SMA-A4 DC isolator	1	182.500	5088635

Connection options





VG-BC DC-TS900

U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _o	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP65
Connection cross-section string		0.5 - 10
Connection cross-section PE		0.5 - 10



PV system solution, type 1+2, with MC4 connector for inverter with 1 MPP tracker, 900 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC900S1	900	For one MPP and with MC4 connection	1	105.000	5088564


System solution, type 1+2, with MC4 connector for photovoltaic inverter with one MPP tracker

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Type 1+2 combination arrester for lightning protection equipotential bonding to EN 62305 (VDE 0185-305)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- One PV string input (MC4 plug connector) at one MPP inverter input, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for use outside

For DC protection of the inverter of photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!



VG-BC900S1	
U max DC	U _c DC 900 V
SPD to EN 61643-11	Type 1+2
Lightning protection zone LPZ	0→2
Impulse discharge current (10/350)	I _{imp} 7 kA
Nominal discharge current (8/20)	I _n 30 kA
Maximum discharge current (8/20 μs)	I _{max} 50 kA
Protection level	U _p < 3,0 kV
Response time	t _A < 25 ns
Temperature range	θ -40 - +80 °C
Protection rating	IP66

Connection options





PV system solution, type 1+2, with MC4 connector for inverter with 2 MPP trackers, 900 V DC




System solution, type 1+2, with MC4 connector for photovoltaic inverter with 2 separate MPP trackers

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Type 1+2 combination arrester for lightning protection equipotential bonding to EN 62305 (VDE 0185-305)
- Low DC voltage protection level: < 3.0 kV (Voc max = 900V DC with V25-B+C/0-450PV)
- One PV string input (MC4 plug connector) at one MPP inverter input, up to 30A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside

For DC protection of the inverter of photovoltaic systems.
If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	Max. continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC900S11	900	For two MPPs and with MC4 connection	1	199.000	5088565

Connection options





VG-BC900S11

U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0-2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _o	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP66



PV housing for inverter with 3 MPP trackers, type 1+2, 900 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
VG-BC DCPH900-31	900	For three MPP and with MC4 connection	1	542.000	5088629

System solution with MC4 connector for photovoltaic inverter with 3 separate MPP trackers


- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC protection level: < 3.0 kV (Voc max = 900 V DC with V25-B+C/0-450PV)
- Two PV string inputs (MC4 plug connector) at one MPP inverter input, up to 30 A DC per terminal
- Pre-mounted in polycarbonate housing (IP65), UV-resistant for the use outside

For DC protection of the inverter of photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

VG-BC DCPH900-31


U max DC	U _c DC	900 V
SPD to EN 61643-11		Type 1+2
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I _{imp}	7 kA
Nominal discharge current (8/20)	I _n	30 kA
Maximum discharge current (8/20 μs)	I _{max}	60 kA
Protection level	U _p	< 3,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP65

Connection options





PV system solution, type 2, with MC4 connector for inverter with 1 MPP tracker, 1,000 V DC




System solution, type 2, with MC4 connector for photovoltaic inverter with 1 MPP tracker

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC voltage protection level: < 4.0 kV (Voc max = 1,000V DC with V20-C/0-500PV)
- One PV string input (MC4 plug connector) at one MPP inverter input, up to 30A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside

For DC protection of the inverter of photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
PVG-C1000S100	1000	For one MPP tracker and with MC4 connection	1	105.000	5088554



Connection options



PVG-C1000S100		
U max DC	U _c DC	1000 V
SPD to EN 61643-11		Type 2
Lightning protection zone LPZ		1→2
Impulse discharge current (10/350)	I _{imp}	— kA
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _p	< 4,0 kV
Response time	t _A	< 25 ns
Temperature range	θ	-40 - +80 °C
Protection rating		IP66



PV system solution, type 2, with MC4 connector for inverter with 2 MPP trackers, 1,000 V DC



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
PVG-C1000S110	1000	For two MPP trackers and with MC4 connection	1	199.000	5088556


System solution, type 2, with MC4 connector for photovoltaic inverter with 2 separate MPP trackers

- Varistor arrester, connectable with cut-off unit in error-resistant Y circuit to VDE 0100-712 (50539-12)
- Low DC voltage protection level: < 4.0 kV (Voc max = 1,000V DC with V20-C/0-500PV)
- One PV string input (MC4 plug connector) at one MPP inverter input, up to 30A DC per terminal
- Pre-mounted in polycarbonate housing (IP66), UV-resistant for use outside

For DC protection of the inverter of photovoltaic systems. If there is a danger of condensation forming through wind, ice, temperature or sunlight, further measures may be necessary!


PVG-C1000S110	
U max DC	U _c DC 1000 V
SPD to EN 61643-11	—
Lightning protection zone LPZ	1→2
Impulse discharge current (10/350)	I _{imp} — kA
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 4,0 kV
Response time	t _A < 25 ns
Temperature range	ϑ -40 - +80 °C
Protection rating	IP66

Connection options





PV CombiController V50, plug-in arrester, type 1+2



CombiController upper part – type 1+2, combination arrester for photovoltaic systems

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 12.5 kA (10/350) and 50 kA (8/20) per pole
- Low DC voltage protection level: < 1.3 kV per pole (Y circuit: 2.6 kV and Voc max = 600 V DC)
- Plug-in arrester with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings
- High current carrying capacity with long lifespan

Application: PV systems with lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V50-B+C 0-300PV	300	1-pole, PV upper part with Y base to 600 V DC	1	8.200	5093726

Connection options




V50-B+C 0-300PV		
U max DC	U _e DC	300 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0-2
Nominal discharge current (8/20)	I _n	30 kA
Impulse discharge current (10/350)	I _{imp}	12.5 kA
Maximum discharge current (8/20 μs)	I _{max}	50 kA
Protection level	U _p	< 1,3 kV
Response time	t _A	<25 ns
Maximum back-up fuse		125 A
Temperature range	ϑ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1

Schutzinstallationen: Überspannungsschutz und Explosionsschutz / en / 2021/06/25 09:52:32 (LLExpert_02926) / 2021/06/25

Surge protection

PV CombiController V25, plug-in arrester, type 1+2



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V25-B+C 0-450PV	450	1-pole, PV upper part with Y base to 900 V DC	1	9.500	5097065

CombiController upper part - type 1+2, combination arrester for photovoltaic systems

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 7 kA (10/350) and 50 kA (8/20) per pole
- Low DC voltage protection level: < 1.5 kV per pole (Y circuit: 3.0 kV and Voc max = 900 V DC)
- Plug-in arrester with thermodynamic cut-off unit and visual function display
- Encapsulated, zinc oxide varistor arrester for use in distributor housings
- High current carrying capacity with long lifespan

Application: PV systems with lightning protection system


V25-B+C 0-450PV	
U max DC	U _c DC 450 V
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-11	Class I+II
Lightning protection zone LPZ	0-2
Nominal discharge current (8/20)	I _n 30 kA
Impulse discharge current (10/350)	I _{imp} 7 kA
Maximum discharge current (8/20 μs)	I _{max} 50 kA
Protection level	U _p < 1,5 kV
Response time	t _A < 25 ns
Maximum back-up fuse	160 A
Temperature range	θ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17.5 mm)	1

Connection options





PV SurgeController V20, plug-in arrester, type 2



SurgeController upper part - type 2, surge arrester for photovoltaic systems

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC voltage protection level: < 1.3 kV per pole (Y circuit: 2.6 kV and Voc max = 600 V DC)
- Plug-in arrester with thermodynamic cut-off unit and visual function display
- Encapsulated, non-extinguishing zinc oxide varistor arrester for use in distributor housings
- High current carrying capacity with long lifespan

Application example: PV systems with or without separated insulated lightning protection system

Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 0-300PV	300	1-pole, PV upper part with Y base to 600 V DC	1	5.500	5099611


Connection options



V20-C 0-300PV		
U max DC	U _c DC	300 V
SPD to EN 61643-11		Type 2
SPD to IEC 61643-11		Class II
Lightning protection zone LPZ		1→2
Nominal discharge current (8/20)	I _n	20 kA
Maximum discharge current (8/20 μs)	I _{max}	40 kA
Protection level	U _o	< 1,3 kV
Response time	t _A	< 25 ns
Maximum back-up fuse		125 A
Temperature range	θ	-40 - +80 °C
Protection rating		IP 20
Division unit TE (17.5 mm)		1



PV SurgeController V20, plug-in arrester, type 2



Type	U max DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
V20-C 0-500PV	500	1-pole, PV upper part with Y base to 1,000 V DC	1	6.500	5099708

SurgeController upper part - type 2, surge arrester for photovoltaic systems


- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Arresting capacity to 40 kA (8/20) per pole
- Low DC voltage protection level: < 2.0 kV per pole (Y circuit: 4.0 kV and Voc max = 1,000 V DC)
- Plug-in arrester with thermodynamic cut-off unit and visual function display
- Encapsulated, non-extinguishing zinc oxide varistor arrester for use in distributor housings
- High current carrying capacity with long lifespan

Application example: PV systems with or without separated insulated lightning protection system

V20-C 0-500PV	
U max DC	U _c DC 500 V
SPD to EN 61643-11	Type 2
SPD to IEC 61643-11	Class II
Lightning protection zone LPZ	1→2
Nominal discharge current (8/20)	I _n 20 kA
Maximum discharge current (8/20 μs)	I _{max} 40 kA
Protection level	U _p < 2,0 kV
Response time	t _A < 25 ns
Maximum back-up fuse	125 A
Temperature range	ϑ -40 - +80 °C
Protection rating	IP 20
Division unit TE (17,5 mm)	1

Connection options





LSC I+II lightning strike and surge counter

Lightning strike and surge counter for the recording of lightning and impulse currents with date and time



IP65 – suitable for outdoor use

Tested to EN/IEC 62561-6

Lightning strike and surge counter can count up to 999 lightning occurrences noting date and time

Exchangeable lithium battery with a lifespan of up to 5 years

Metering range 1 to 100 kA

The LSC I+II lightning current meter measures and permanently saves lightning and pulse currents (10/350), (8/20) and saves this event together with the date and time. This ensures constant monitoring in order to notice if any lightning has struck the lightning protection system or whether there have

been any surge voltages in the system. If a lightning or surge voltage event has occurred, then the entire lightning protection system must be maintained according to VDE 0185-305 (IEC 62305).


Lightning strike counter



Type	Measuring range	Pack Piece	Weight kg/100 pc.	Item no.
LSC I+II	1 kA - 100 kA	1	32.500	5091722

The LSC I+II lightning current meter measures and permanently saves pulse currents, together with the date and time. This ensures constant monitoring in order to notice if any lightning has struck the lightning protection system. Should this be the case, then the lightning protection system must be maintained according to VDE 0185-305 (IEC 62305).

- Saving and display of time and date
- Usable both inside and outside due to its protection class of IP65
- Cable clip for round conductor or flat conductor
- Direct mounting on the conductor or the PE conductor of the surge protective device
- Long lifespan of the internal lithium batteries
- LCD display
- Internal battery
- Tested according to VDE 0185-561-6 (IEC 62561-6)



Testing devices



ISOLAB measuring system arrester tester


Type	Country version	Nom. voltage V	Measuring range	Pack Piece	Weight kg/100 pc.	Item no.
ISOLAB	D/GB	6	0V - 999V	1	75.000	5096812

To test the insulation resistance to DIN VDE 0100 Part 610 and the characteristic curve behaviour of the following surge voltage and lightning current arresters:

- V10-C and V20-C: Uc Tolerance range
 - 75 V -> 110 V - 130 V
 - 150 V -> 215 V - 265 V
 - 280 V -> 385 V - 475 V
 - 320 V -> 460 V - 560 V
 - 335 V -> 460 V - 560 V
 - 385 V -> 560 V - 680 V
 - 440 V -> 645 V - 785 V
 - 550 V -> 820 V - 1,000 V

- V25-B+C and V50-B+C: Uc Tolerance range
 - 150 V -> 215 V - 265 V
 - 280 V -> 385 V - 475 V
 - 320 V -> 460 V - 560 V
 - 385 V -> 560 V - 680 V


- Varistor arresters of other manufacturers can be tested for 1 or 3 mA characteristic curve behaviour
- Battery operation
- Measuring cables contained in the scope of delivery.




Testing unit for lightning barriers

Type	Pack Piece	Weight kg/100 pc.	Item no.
LFC	1	164.500	5096786

OBO Life Control allows function control of the MDP lightning barriers. The lightning barriers can be checked while installed. Life Control will not have any influences on the measuring signal. Life Control possesses an integrated OLED with visual and acoustic defect signalling. A separate LED inside the testing pin is also integrated. Life Control is delivered in a case, complete with a CD and instructions.



Card reader PCS-CS..



Type	Country version	Nom. voltage V	Measuring range	Measuring tolerances	Pack Piece	Weight kg/100 pc.	Item no.
PCS-CS-D	EN	230	3--120 kA	<2 kA (<2%)	1	750.000	5091683

Magnetic card reader for reading and analysing PCS cards.

- Inc. rechargeable battery for 4 h continuous, no-mains operation
- Large, clear display

Magnetic cards and holders



Magnetic card PCS




Type	Pack PU	Weight kg/100 PUs	Item no.
PCS	1	5.000	5091438

Peak Current Sensor (PCS) card for recording pulsed/lightning currents. A continuous check of whether lightning has struck the lightning protection system and how high the most recent lightning current was in kA can be carried out easily by the system operator, a specialist lightning protection company or by a surveyor. Here, the printed maintenance circuit and the labelling panels support the maintenance work of the entire lightning protection system, which must be performed at defined intervals according to VDE 0185-305-3 (IEC/EN 62305-3).

- Contents = 10 pieces
- Digital evaluation via the PCS card reading device
- Can be used in addition to the OBO lightning current meter LSC I-II
- With separate labelling panels: "Erected by", "Tested by", "Card code"
- Integrated maintenance circuit (year/month)

Magnetic card and holder MK-B



Type	Pack PU	Weight kg/100 PUs	Item no.
MK-B	1	31.000	5091322

PCS magnetic card to record pulse/lightning currents including holder

- Holder can be leaded
- For mounting on round conductor Rd 8-10
- Simple holder mounting through clamping
- 1 PU = 10 units






Magnetic card holder PCS-H


Type	Pack PU	Weight kg/100 PUs	Item no.
PCS-H	1	31.000	5091527

Magnetic card holder for mounting PCS cards.

- Sealable holder
- For installing on round conductor Rd 8-10
- Simple holder installation by means of clamp
- 1 PU = 10 pieces



Coordinated Lightning Controller, plug-in arrester




Highest continuous voltage				Pack	Weight	
Type	V	Version		Piece	kg/100 pc.	Item no.
MCD 50-B 0	255	1-pole		1	19.200	5096822

Combination arrester type 1+2

- Lightning current arresting capacity 50 kA (10/350)
- Protection level < 1.7 kV
- Line current quenching capacity 10 kA
- Encapsulated, non-extinguishing spark gap

Application: Industrial systems and buildings with external lightning protection of classes I to IV.


Connection options



MCD 50-B 0

Nominal voltage	U_N	230 V
SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
Lightning protection zone LPZ		0→2
Impulse discharge current (10/350)	I_{imp}	50 kA
Lightning surge current (10/350)	I_{total}	50 kA
Nominal discharge current (8/20)	I_n	50 kA
Arrestor surge current (8/20) [total]	$I_{Total 8/20}$	50 kA
Protection level	U_d	< 1,7 kV
Response time	t_A	<100 ns
Follow current quenching capacity leff	$I_{fi eff}$	10 kA
Maximum back-up fuse		500 A
Temperature range	ϑ	-40 - +85 °C
Division unit TE (17.5 mm)		2
Protection rating		IP20
Approvals		VDE
Connection cross-section, rigid		10 - 50 mm ²
Connection cross-section, multi-wire		10 - 35 mm ²
Connection cross-section, flexible		10 - 25 mm ²

Plug-in arrester NPE-C50



Max. continuous voltage				Pack	Weight	
Type	AC V	Pole version	Protection rating	Piece	kg/100 pc.	Item no.
C50-0-255	255	N/PE	IP20	1	7.215	5095609

Upper part NPE, lightning current combination arrester, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity up to 50 kA (10/350) in total
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic according to UL 94 V-0

Connection options




C50-0-255

SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
SPD to UL 1449		Type 4
Maximum continuous voltage AC	U_C	255 V
Nominal discharge current (8/20 μs)	$I_{n / L-N}$	30 kA
Maximum discharge current (8/20 μs)	I_{max}	50 kA
Lightning surge current (10/350 μs)	I_{imp}	50 kA
Protection level [N-PE]	$U_{d / N-PE}$	1.5 kV
Short-circuit withstand for max. mains-side overcurrent protection		25 kA
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		UL, KEMA, ÖVE, VDE
Conductor cross-section, flexible (fine-wire)		1.5 - 35 mm ²
Conductor cross-section, rigid (single wire/multi-wire)		1.5 - 35 mm ²
Conductor cross-section, flexible (fine-wire)		16 - 2 AWG
Conductor cross-section, rigid (single wire/multi-wire)		16 - 2 AWG



Plug-in arrester V20 280 V

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V20-0-280	280	1	IP20	1	5.000	5095364



Surge arrester, type 2

- For surge protection equipotential bonding to VDE 0100-443 (IEC 60364-4-44)
- Discharge capacity to 40 kA (8/20) per pole through high-performance varistors
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)

V20-0-280


SPD to EN 61643-11		Type 2
SPD to IEC 61643-11		Class II
SPD to UL 1449		Type 4
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	280 V
Protection level	U_p	1.3 kV
Nominal discharge current (8/20 μ s)	$I_n / L-N$	20 kA
Maximum discharge current (8/20 μ s)	I_{max}	40 kA
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		UL, ÖVE, VDE, KEMA

Connection options



Plug-in arrester V50 280 V

Type	Max. continuous voltage AC V	Pole version	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
V50-0-280	280	1	IP20	1	8.500	5093508




Combination arrester, type 1+2

- For lightning protection equipotential bonding to VDE 0185-305 (IEC 62305)
- Lightning current discharge capacity of 12.5 kA (10/350) per pole
- Modular, plug-in arrester with dynamic cut-off unit and visual status display
- Locking mechanism with vibration protection and voltage keying
- Plastic (UL 94 V-0)


V50-0-280

SPD to EN 61643-11		Type 1+2
SPD to IEC 61643-11		Class I+II
SPD to UL 1449		Type 4
Nominal voltage AC (50/60 Hz)	U_n	230 V
Maximum continuous voltage AC	U_c	280 V
Lightning surge current (10/350 μ s)	I_{imp}	12.5 kA
Nominal discharge current (8/20 μ s)	$I_n / L-N$	30 kA
Maximum discharge current (8/20 μ s)	I_{max}	50 kA
Short-circuit withstand for max. mains-side overcurrent protection		50 kA eff
Operating temperature range	T_u	-40 - +80 °C
Protection rating		IP20
Approvals		UL, KEMA, ÖVE, VDE

Connection options



Connection terminal for through-wiring




Type	Colour	Version	Pack Piece	Weight kg/100 pc.	Item no.
AS 3x16	Light grey	3 x 16 mm ²	5	2.474	5012010

Connection terminal type: AS 3 x 16
 Connection cross-section: 3 x 1.5 - 16 mm² rigid/ multiple strands
 3 x 1.5 - 10 mm² fine-wire/with wire end sleeve
 Stripping length: 16 mm
 Rec. tightening torque: 1.2 Nm
 Nominal current: 50 A
 Width: 17.5 mm (1 PU)

For EMC-optimised V through-wiring to IEC 60364-5-53 (VDE 0100-534).

Accessories for lightning current arrester

Cu




Type	Pack Piece	Weight kg/100 pc.	Item no.
MC V3	10	1.700	5096884
MC V4	10	2.300	5096886

Copper bridge 16 mm², suitable for bridging MC arresters in side channel.

- V3 for 3-pole circuits
- V4 for 4-pole circuits

Connecting bridge for V10 Compact 200 mm




Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
VB-V10 COMPACT-2	200 mm	1	5.300	5089650

To bridge V10 Compact e.g. to FI protection switches in a 17.5 mm grid.

- 4-pole version (L1; L2; L3; N)
- Conductor: H07V-K 4 mm²
- V10 Compact connection via pin contact (diameter: 2.7 mm)
- FI protection switch connection via flat contact (4 x 1.5 mm)


Copper bridge with step width 17.6 mm



Type	Pack Piece	Weight kg/100 pc.	Item no.
KB MB	10	0.900	5089660

The bridges KB... permit parallel connection of bases and poles of the MultiBase bases.
 The bridges are available in various widths.

Copper bridge with step width 17.6 mm



Type	Pack Piece	Weight kg/100 pc.	Item no.
KB MB	10	1.470	5089662

The bridges KB... permit parallel connection of bases and poles of the MultiBase bases.
 The bridges are available in various widths.

VA




Mounting plate, 1-pole

Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF-MS-P1	1-pole	1	19.600	5096992

Mounting plate 1-pole

- Mounting plate for installation of the arrester MCF 35-1+FS-440
- Prefabricated hole pattern for mounting the arrester on busbars
- Required screws for installation of the arrester enclosed



VA




Mounting plate, 1-pole, M10

Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF-MS-M10	1-pole	1	14.200	5096990

Mounting plate with threaded connector M10

- Mounting plate with threaded M10 connector to install the arrester MCF 35-1+FS-440
- M10 bolts for direct installation of the arrester on busbars
- Required screws for installation enclosed



VA




Mounting plate, 3-pole

Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
MCF-MS-P3	3-pole	1	99.800	5096994

Mounting plate 3-pole

- Mounting plate 3-pole for installation of the arrester MCF 35-1+FS-440
- Prefabricated hole pattern for mounting the arrester on busbars
- Suitable for wall mounting
- Required screws for installation enclosed




Empty housing for arrestors




Replacement connector for VF remote signalling

Type	Version	Pack Piece	Weight kg/100 pc.	Item no.
VF-FS	3-pole	25	0.320	5098475

Replacement telephony connector, 3-pin version, for VF variant



Earthing strip




Type	Pack Piece	Weight kg/100 pc.	Item no.
VB-MDP 10-MD	1	2.300	5098470

Connecting bridge for 8 mm lightning barriers

- Length of bridge can be adjusted
- Material: Copper
- Allows quick equipotential bonding

Application: Parallel switching of the MDP lightning barriers

Voltage tap for MCF-NAR series




Type	Nominal voltage AC (50/60 Hz) V	Protection rating	Pack Piece	Weight kg/100 pc.	Item no.
MCF-NAR-SMG	230	IP20	1	5.850	5096900


Adapter for voltage tap in power-side connection compartment

- Simple and space-saving voltage taps for the termination point meter position (APZ) and the space for additional applications (RfZ)
- With spring contacts for easy connection of wires
- Includes 2 plug sockets
- Safety screw to prevent unwanted loosening
- Replaceable 5 A fine-wire fuse with a breaking capacity of 50 kA
- Fuse holder 6,3 x 32 mm





Explosion protection



Explosion protection

	Surge protection	222
	Spark gaps	232
	Equipotential bonding	236
	Conductors	240



MDP Ex family

MCR protection for Ex areas




- Protection device for multi-wire systems (4-pole)
- Direct shield earthing
- Easy-mounting, screwless connection option
- Space-saving width of just 8.7 mm
- Ex-tested for intrinsically safe measuring circuits
- High frequency bandwidth up to 100 MHz

Surge protection in potentially explosive areas is an important topic. Here, it is important to protect costly measuring technology against the influence of surge voltages through atmospheric discharge. OBO lightning barriers are tested for intrinsic safety

(ia) and are independently certified. With a high arresting capacity of 10 kA, they offer optimum protection for four-pole measurement and control applications. Different voltage variants offer a wide range of applications.



Series protection device, 4-pole, 5 V version




Lightning barrier for intrinsically safe measuring circuits

- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ja Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-5-EX	7	10	4	1	5.800	5098412


Connection options



MDP-4 D-5-EX

Maximum continuous voltage AC	U_c	7 V
Maximum continuous voltage DC	U_c	10 V
Category	Type	1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_L	0.58 A
Series resistance per wire		2,35 Ω \pm 5 %
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		< 35 V
Protection level wire-earth		< 800 V
Frequency range		0-100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
EX approval		II 2(1)G Ex ia [ja Ga] IIC T4 Gb
Testing standard		IEC 61643-21
Approvals		UL

Series protection device, 4-pole, 24 V version



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-24-EX	20	28	4	1	5.800	5098432

Lightning barrier for intrinsically safe measuring circuits


- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

MDP-4 D-24-EX


Maximum continuous voltage AC	U_c	20 V
Maximum continuous voltage DC	U_c	28 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_L	0.58 A
Series resistance per wire		2,35 $\Omega \pm 5\%$
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		< 55 V
Protection level wire-earth		<800 V
Frequency range		0-100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
EX approval		II 2(1)G Ex ia [ia Ga] IIC T4 Gb
Testing standard		IEC 61643-21
Approvals		UL

Connection options





Series protection device, 4-pole, 48 V version




Lightning barrier for intrinsically safe measuring circuits

- Protection device for multi-wire systems
- Direct shield earthing and screwless connection terminals
- Space-saving width of just 8.7 mm
- High frequency range of 0–100 MHz
- ATEX approval: II 2(1) G Ex ia [ja Ga] IIC T4 (BVS 11 ATEX E 131 X)
- UL-listed (4UM2)

Application: Universal use on 35 mm DIN profile rail in any standard distribution housing.

Type	Max. continuous AC voltage V	Max. continuous DC voltage V	Number of poles	Pack Piece	Weight kg/100 pc.	Item no.
MDP-4 D-48-EX	41	58	4	1	5.800	5098452

Connection options

**MDP-4 D-48-EX**

Maximum continuous voltage AC	U_c	41 V
Maximum continuous voltage DC	U_c	58 V
Category		Type 1+2+3 / D1+C2+C1
Lightning protection zone LPZ		0→3
Number of poles		4
Rated current	I_L	0.58 A
Series resistance per wire		2,35 Ω \pm 5 %
Impulse durability wire-wire		C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth		C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)		10 kA
Total discharge current (10/350)		D1: 2 kA
Protection level wire-wire		< 95 V
Protection level wire-earth		< 800 V
Frequency range		0-100 MHz
Temperature range	ϑ	-40 - +80 °C
Installation type		DIN rail
Connection system		Terminal
Protection rating		IP20
Shielding connection available		Yes
Shield connection		Direct
Connection cross-section, flexible		0.14 - 2.5 mm ²
Connection cross-section, multi-wire		0.14 - 1.5 mm ²
Connection cross-section, rigid		0.14 - 2.5 mm ²
Earthing via:		DIN rail
EX approval		II 2(1)G Ex ia [ja Ga] IIC T4 Gb
Testing standard		IEC 61643-21
Approvals		UL

Petrol Field Protector FDB

MCR protection for explosive areas





- For potentially explosive areas
- Two or three-pole protection of various sensors
- Metric or NPT thread
- Robust VA housing
- High arresting capacity

With the Petrol Field Protector for data cable protection devices, OBO Bettermann can offer a surge protective device for sensors in potentially explosive areas. The Petrol Field Protector permits two or three-pole protection of all kinds of sensors. The protection device can be fastened directly on the sensor and wired in using the appropriate metric or

NPT thread. The robust VA housing means that aggressive atmospheres are no problem. The intrinsic safety of the Petrol Field Protector has been independently tested and certified. The Petrol Field Protector is your partner for safety-relevant applications in which effective surge protection must be guaranteed.



Protection for field devices, 2-pole, 24 V, metric




Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems

- Metric connection technology
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ja Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-2 24-M	22	32	2-pole; metric	1	18.500	5098380

Connection options



FDB-2 24-M	
Maximum continuous voltage AC	U_c 22 V
Maximum continuous voltage DC	U_c 32 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Number of poles	2
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<80 V
Protection level wire-earth	<800 V
Temperature range	ϑ -20 - +70 °C
Installation type	Screw-on
Protection rating	IP65/67
Mounting of input / output	M20 x 1.5 external thread
Mounting of field / device side:	Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:	Connection cable
Housing material	V2A
EX approval	II 2(1)G Ex ia [ja Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard	IEC 61643-21

Protection for field devices, 3-pole, 24 V, metric



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-3 24-M	22	32	3-pole; metric	1	19.000	5098382


Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems

- Metric connection technology
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors



FDB-3 24-M	
Maximum continuous voltage AC	U_c 22 V
Maximum continuous voltage DC	U_c 32 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1→3
Number of poles	3
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<80 V
Protection level wire-earth	<800 V
Temperature range	ϑ -20 - +70 °C
Installation type	Screw-on
Protection rating	IP65/67
Mounting of input / output	M20 x 1.5 external thread
Mounting of field / device side:	Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:	Connection cable
Housing material	V2A
EX approval	II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard	IEC 61643-21

Connection options





Protection for field devices, 2-pole, 24 V, NPT




Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems

- NPT connection technology
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-2 24-N	22	32	2-pole; NPT	1	19.000	5098390

Connection options



FDB-2 24-N	
Maximum continuous voltage AC	U_c 22 V
Maximum continuous voltage DC	U_c 32 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Number of poles	2
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<80 V
Protection level wire-earth	<800 V
Temperature range	ϑ -20 - +70 °C
Installation type	Screw-on
Protection rating	IP65/67
Mounting of input / output	1/2" NPT
Mounting of field / device side:	Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:	Connection cable
Housing material	V2A
EX approval	II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard	IEC 61643-21

Protection for field devices, 3-pole, 24 V, NPT



Type	Max. continuous voltage AC V	Max. continuous voltage DC V	Version	Pack Piece	Weight kg/100 pc.	Item no.
FDB-3 24-N	22	32	3-pole; NPT	1	19.500	5098392


Petrol Field Protector FDB for intrinsically safe measuring circuits and bus systems


- NPT connection technology
- Low protection level at high current load
- Easy mounting on field devices
- Negligible internal capacitance and inductance
- Stainless steel housing with pressure-resistant encapsulation
- ATEX approval: II 2(1) G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)

Application: Flow sensors, temperature sensors


FDB-3 24-N	
Maximum continuous voltage AC	U_c 22 V
Maximum continuous voltage DC	U_c 32 V
Category	Type 2+3 / C2+C1
Lightning protection zone LPZ	1-3
Number of poles	3
Impulse durability wire-wire	C1: 0,5 kV / 0,25 kA (8/20 μ s)
Impulse durability wire-earth	C2: 5 kV / 2,5 kA (8/20 μ s)
Total discharge current (8/20)	10 kA
Protection level wire-wire	<80 V
Protection level wire-earth	<800 V
Temperature range	ϑ -20 - +70 °C
Installation type	Screw-on
Protection rating	IP65/67
Mounting of input / output	1/2" NPT
Mounting of field / device side:	Connection cable 1.5 mm ² Length ~ 250 mm
Earthing via:	Connection cable
Housing material	V2A
EX approval	II 2(1)G Ex ia [ia Ga] IIC T4..T6 Gb (BVS 10 ATEX E 048)
Testing standard	IEC 61643-21

Connection options





EX ISG H spark gap




Type	Pack Piece	Weight kg/100 pc.	Item no.
EX ISG H	1	41.360	5240030

- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIC T80 °C Db IP67


Application: In potentially explosive areas zone 1/21 and 2/22, indirect bridging of insulating flanges and insulating glands, e.g. in cathodic, corrosion-protected (KKS) systems.

EX ISG H		
Connecting cable length		0 m
Rated impulse sparkover voltage	$U_{r,imp}$	1.25 kV
Rated DC withstand voltage	U_{wDC}	354 V
Rated power frequency withstand voltage	U_{wAC}	250 V
Power frequency spark-over voltage	U_{AS}	0.56 kV
Impulse discharge current (10/350)	I_{imp}	100 kA
Nominal discharge current (8/20)	I_n	100 kA
Lightning current carrying capacity		H/100 kA
Temperature range	ϑ	-20 - +60 °C

Connection options



ES ISG H spark gap, with one cable




- Spark gap to VDE 0185-561-3 (IEC 62561-3)
- Ex certificate to ATEX
- Labelling to EN 60079-0/-1: II 2 G Ex db IIC T6 Gb
- Labelling to EN 60079-0/-31: II 2 D Ex td IIIC T80 °C Db IP67
- Ex certificate to IECEx
- Labelling to IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to IEC 60079-0/-31: Ex td IIIC T80 °C Db IP67
- Ex certificate to INMETRO
- Labelling to ABNT NBR IEC 60079-0/-1: Ex db IIC T6 Gb
- Labelling to ABNT NBR IEC 60079-31: Ex td IIIC T80 °C Db IP67

Application: In potentially explosive areas zone 1/21 and 2/22, indirect bridging of insulating flanges and insulating glands, e.g. in cathodic, corrosion-protected (KKS) systems.

Type	Pack Piece	Weight kg/100 pc.	Item no.
EX ISG H 350	1	57.260	5240031

Connection options



EX ISG H 350		
Connecting cable length		0.35 m
Rated impulse sparkover voltage	$U_{f \text{ imp}}$	1.25 kV
Rated DC withstand voltage	U_{wDC}	354 V
Rated power frequency withstand voltage	U_{wAC}	250 V
Power frequency spark-over voltage	U_{AS}	0.56 kV
Impulse discharge current (10/350)	I_{imp}	100 kA
Nominal discharge current (8/20)	I_n	100 kA
Lightning current carrying capacity		H/100 kA
Temperature range	ϑ	-20 - +60 °C

Connection components

Cu

Connection cable – AL EX ISG


Type	Dimension mm	Pack Piece	Weight kg/100 pc.	Item no.
AL EX ISG 100	100	1	9.600	5240102
AL EX ISG 200	200	1	12.300	5240104
AL EX ISG 300	300	1	15.200	5240106

UV-resistant connection cable (copper 25 mm²) for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces. With cable shoe for M10 bolts on both sides, on one side with M10 screw, nuts and spring ring.



Connection clamp AB EX ISG straight

St FT




Type	Drill hole		Pack Piece	Weight kg/100 pc.	Item no.
	Ø mm	Version			
AB EX ISG S M10	11	For M10 bolt	2	9.000	5240360
AB EX ISG S M12	14	For M12 bolt	2	8.900	5240362
AB EX ISG S M16	18	For M16 bolt	2	8.600	5240366
AB EX ISG S M20	22	For M20 bolt	2	8.200	5240370
AB EX ISG S M24	26	For M24 bolt	2	7.800	5240374

Connection clamp for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces.


Connection clamp AB EX ISG, angled

St FT




Type	Drill hole		Pack Piece	Weight kg/100 pc.	Item no.
	Ø mm	Version			
AB EX ISG SW M10	11	For M10 bolt	2	10.900	5240380
AB EX ISG SW M12	14	For M12 bolt	2	10.800	5240382
AB EX ISG SW M16	18	For M16 bolt	2	10.500	5240386
AB EX ISG SW M20	22	For M20 bolt	2	10.100	5240390
AB EX ISG SW M24	26	For M24 bolt	2	9.700	5240394

Connection clamp for mounting the OBO Ex spark gap, type EX ISG, on insulating flanges and insulating pieces.



Safe together

The EX BES earthing pipe clamp augments the OBO portfolio for equipotential bonding in potentially explosive areas



Ignition spark-free lightning protection equipotential bonding – indoor and outdoor application


The earthing pipe clamp for Ex areas augments the OBO portfolio for equipotential bonding in potentially explosive areas. Like the EX BES, the EX PAS equipotential busbar has been independently tested in compliance with VDE 0185-561-1 (EN / IEC 62561-1) and independently certified for every explosion group in Ex zones 1/21 and 2/22.

- For pipes of 6–500 mm outer diameter
- UV-stabilised and halogen-free plastic hood
- Screws prevented from loosening as defined in VDE 0185-305-3 Supplement 2
- Suitable for indoor and outdoor applications



VA

Equipotential busbar for EX zone 1/21, 2/22




For ignition spark-free protection/functional equipotential bonding to DIN VDE 0100-410/-540 as well as ignition spark-free lightning protection equipotential bonding to VDE 0185-305 (IEC 62305) in systems to VDE 0165-1 (IEC/ EN 60079-14)

- Use in potentially explosive areas, Ex zone 1 and 2/21 and 22
- Tested according to explosion group IIC
- Lightning current carrying capacity class H (100 kA) to VDE 0185-561-1 (IEC/EN 62561-1)
- UV-stabilised and halogen-free insulation feet
- With spring washer for locking screws against self-loosening to VDE 0185-305-3 Supplementary sheet 2
- Suitable for indoor and outdoor applications

Type	Number of connections	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
EX PAS 5	5	H/100	1	152.000	5015265

VA

Equipotential busbar for EX zone 1/21, 2/22




For ignition spark-free protection/functional equipotential bonding to DIN VDE 0100-410/-540 as well as ignition spark-free lightning protection equipotential bonding to VDE 0185-305 (IEC 62305) in systems to VDE 0165-1 (IEC/ EN 60079-14)

- Use in potentially explosive areas, Ex zone 1 and 2/21 and 22
- Tested according to explosion group IIC
- Lightning current carrying capacity class H (100 kA) to VDE 0185-561-1 (IEC/EN 62561-1)
- UV-stabilised and halogen-free insulation feet
- With spring washer for locking screws against self-loosening to VDE 0185-305-3 Supplementary sheet 2
- Suitable for indoor and outdoor applications

Type	Number of connections	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
EX PAS 10	10	H/100	1	214.000	5015270



Earthing pipe clamp for EX Zone 1/21, 2/22



Type	For pipe Ø mm	Dim. L mm	Lightning current carrying capacity kA	Pack Piece	Weight kg/100 pc.	Item no.
EX BES 28	6-28	215	H/100	1	30.580	5057630
EX BES 300	28-300	1170	H/100	1	35.800	5057640
EX BES 500	300-500	1800	H/100	1	39.430	5057645


For ignition spark-free protection/functional equipotential bonding according to DIN VDE 0100-410/-540 and ignition spark-free lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305) in systems according to VDE 0165-1 (IEC/EN 60079-14).

- For pipes of 6–500 mm external diameter
- Use in potentially explosive areas, Ex zone 1 and 2/21 and 22
- Tested according to explosion group IIC
- Lightning current carrying capacity class H (100 kA) to VDE 0185-561-1 (IEC/EN 62561-1)
- UV-stabilised and halogen-free plastic hood
- Secured with bolts against self-loosening to VDE 0185-305-3, Supplementary Sheet 2
- Suitable for indoor and outdoor applications

Tool


VA

Pre-tensioning tool



Type	Dim. L mm	Dim. b mm	Pack Piece	Weight kg/100 pc.	Item no.
927 BES VSW 25	153	73	1	14.700	5057690


To tension earthing pipes and earthing pipe clamps.



isCon® conductor, Professional plus light grey



Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon Pro+ 75 GR	35	26	0.75	25	86.800	5407995
isCon Pro+ 75 GR	35	26	0.75	100	86.800	5407997




Please refer to the mounting instructions for information on routing the OBO isCon® conductor.

- Highly voltage-resistant, insulated arrester
- Protection against contact voltage during rain (VDE 0432-1 (IEC/EN 60060-1))
- Floating discharge-free
- Additional mechanical protection (double protective jacket)
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.75$ m (air) and $se \leq 1.5$ (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 5.1 kWh/m
- Protection against contact voltage under sprinkling (VDE 0432-1 (IEC/EN 60060-1))
- Can be used in potentially explosive areas Ex zone 1/2 and 21/22 when taking the current mounting instructions into account

isCon® conductor, Professional plus black

Type	Cross-section mm ²	Nominal size Ø mm	Equivalent separation distance m	Pack m	Weight kg/100 m	Item no.
isCon Pro+ 75 SW	35	23	0.75	25	69.400	5408002
isCon Pro+ 75 SW	35	23	0.75	100	69.400	5408004
isCon Pro+ 75 SW	35	23	0.75	250	69.400	5408006




Please refer to the mounting instructions for information on routing the OBO isCon® conductor.

- Highly voltage-resistant, insulated conductor
- Floating discharge-free
- Additional mechanical protection (black protective jacket)
- For maintenance of the separation distance according to IEC 62305 (VDE 0185-305-3)
- Tested according to IEC/EN 62561-1 (VDE 0185-561-1) with H1/150 kA
- Equivalent separation distance $se \leq 0.75$ m (air) and $se \leq 1.5$ (solid material)
- Tested according to IEC TS 62561-8 (VDE V 0185-561-8)
- Halogen-free
- Fire load 4.3 kWh/m
- Can be used in potentially explosive areas Ex zone 1/2 and 21/22 when taking the current mounting instructions into account





Directories




Directories

	Test marks	244
	Pictogram explanation	246
	Numeric directory	250



Test marks

	American Bureau of Shipping, USA		Underwriters Laboratories Inc., USA + CSA, Canada
	AENOR, Producto Certificado, Spain		Österreichischer Verband für Elektrotechnik, Austria
	STOWARZYSZENIE ELEKTRYKÓW POLSKICH, Poland		ISTITUTO ITALIANO DEL MARCHO DI QUALITÀ, Italy
	Lightning current-tested		RINA 1861, Ship Classification, Certification and Services
	Lightning current-tested, Class H (100 kA)		Underwriters Laboratories Inc., USA
	CEBEC, Belgium		SEMKO An Inchcape Testing Services Company, Sweden
	Canadian Standards Association, Canada		Eidgenössisches Starkstrominspektorat, Switzerland
	DEMKO, Danmarks Elektriske Materielkontrol, Denmark		South African Bureau of Standards
	Deutsches Institut für Bautechnik Berlin, Germany		Shock-tested, Bundesamt für Zivilschutz, Germany
	Det Norske Veritas		Sähköarkastuskeskus Elinspektionscentralen Electrical Inspectorate, Finland
	ENEC Austria		Underwriters Laboratories Inc., USA
	ATEX certificate for explosive areas		Underwriters Laboratories Inc., USA
	ELEKTROTECHNICKÝ ZKUŠEBNÍ ÚSTAV, Czech Republic		Verband der Elektrotechnik, Elektronik, Informationstechnik e.V., Germany
	FIMKO, Finland		German Association of Electricians, tested safety
	Forschungs- und Materialprüfungsanstalt, Germany		5-year warranty
	Russia, GOST The State Committee for Standards		
	Test marks for technical resources, VDE Prüf- und Zertifizierungsinstitut Offenbach, Germany		
	Halogen-free; without chlorine, fluorine and bromine		
	INMETRO, Brazil		
	KEMA-KEUR, Netherlands		
	Indication of metric products		
	MAGYAR ELEKTROTECHNIKAI ELLENŐRZŐ INTÉZET Budapest, Hungary		
	NEMKO, Norway		
	AFNOR Quality symbol of the French standardisation institute		



Pictogram explanation

Surfaces

	Strip galvanised
	Strip galvanised/plastic-coated
	Strip galvanised zinc/aluminium, double dip
	Bright
	Anodised
	Hot-dip galvanised
	Electrogalvanised
	Electrogalvanised/plastic-coated
	Electrogalvanised, yellow-chromated
	Electrogalvanised, yellow passivated
	Electrogalvanised, transparently passivated
	Primed
	Painted
	Welding primed
	Hot-dip galvanised
	Hot-dip galvanised 85 µm
	Copper-plated
	Nickel-plated
	Galvanised, Deltatone 500
	Galvanised, MAGNI 565
	Zinc-aluminium coated, Galfan
	Zinc scale

Conformity symbol

	Communautés Européennes, EC declaration of conformity according to EC directives
	RoHS-conformant

Quality marks

	Halogen-free; without chlorine, fluorine and bromine
	Flame resistant 650 °C
	Flame resistant 750 °C
	Flame resistant 960 °C
	UV-resistant

Specific product symbols

	Diameter 60 mm
	Diameter 68 mm
	Protection device to DIN EN 61643-11 or IEC 61643-11
	Transition from LPZ 2 to LPZ 3
	Acoustic signalling

Applications

	Remote signalling
	Acoustic signalling
	Integrated Service Digital Network, ISDN applications
	Digital Subscriber Line, DSL applications
	Analogue telecommunication
	Category 5 TwisterPair
	Channel Performance to American EIA/TIA standard
	Measuring, controlling and regulating systems
	TV applications
	SAT-TV applications
	MultiBase base
	LifeControl
	Intrinsically safe protection device for potentially explosive areas
	Channel Performance to ISO / IEC 11801
	Power over Ethernet
	230/400 V system
	Protection rating IP 54
	Protection rating IP 65

Lightning protection classes

	Protection device to DIN EN 61643-11 or IEC 61643-11
	Combination protection device made of type 1 and type 2
	Protection device to DIN EN 61643-11 or IEC 61643-11



Lightning protection classes

	Protection device to DIN EN 61643-11 or IEC 61643-11
	Protection device to DIN EN 61643-11 or IEC 61643-11

Lightning protection zone

	Transition from LPZ 0 to LPZ 1
	Transition from LPZ 0 to LPZ 2
	Transition from LPZ 0 to LPZ 3
	Transition from LPZ 1 to LPZ 2
	Transition from LPZ 1 to LPZ 3
	Transition from LPZ 2 to LPZ 3

BSS maintenance of electrical function installation

	Fire-tested systems
	Escape route ceiling mounting with pressure clip
	OBO Grip, wall routing type
	OBO Grip, ceiling routing type
	Pressure clip for maintenance of electrical function, ceiling mounting

BSS anchor

	Fire protection anchor
	Fire protection bolt tie

BSS test marks/material class

	Maintenance of electrical function class E30
	Maintenance of electrical function class E90

Clamp clip base shapes

	Clamp clip for C profile rail, slot width 11–12 mm
	Clamp clip for C profile rail, slot width 16–17 mm
	Clamp clip for C profile rail, slot width 18–22 mm

Diameter

	Diameter 60 mm
	Diameter 68 mm
	Diameter 70 mm
	Diameter 74 mm

Entries

	4 cable entries
	6 cable entries
	7 cable entries
	8 cable entries
	9 cable entries
	10 cable entries
	12 cable entries
	10 cable entries ECO
	12 cable entries ECO
	14 cable entries ECO
	16 cable entries
	18 cable entries ECO
	24 cable entries

Gland thread

	Thread metric
	Thread Pg

Entry size

	M20 entry
	M25 entry
	M32 entry
	M40 entry

KTS side heights

	Cable tray, side height 35 mm
	Cable tray, side height 60 mm
	Cable tray, side height 85 mm
	Mesh cable tray, slant height 35 mm
	Mesh cable tray, slant height 55 mm

Materials

	Flat steel
	Angular steel
	U steel
	Round material



Pictogram explanation

Nominal cross-section

	Nominal cross-section 1.5 mm ²
	Nominal cross-section 1.5–2.5 mm ²
	Nominal cross-section 2.5 mm ²
	Nominal cross-section 2.5–4 mm ²
	Nominal cross-section 4 mm ²
	Nominal cross-section 4–6 mm ²
	Nominal cross-section 6 mm ²
	Nominal cross-section 10 mm ²
	Nominal cross-section 16 mm ²

Nominal voltage

	Nominal voltage 400 V
	Nominal voltage 500 V
	Nominal voltage 660 V

Polarity

	3-pole
	5-pole
	7-pole
	8-pole
	10-pole
	12-pole

Slot widths

	Slot width 7.5 mm
	Slot width 11 mm
	Slot width 11–12 mm
	Slot width 12 mm
	Slot width 15 mm
	Slot width 16 mm
	Slot width 16.5 mm
	Slot width 16–17 mm
	Slot width 17 mm
	Slot width 18 mm
	Slot width 22 mm
	Slot width 35 mm

Screw heads

	Philips screw
	Torx screw
	Phillips screw
	Pozidrive

Firing devices

	Bolt-firing tool
	Nail device

Protection rating

	Protection rating IP 20
	Protection rating IP 30
	Protection rating IP 31
	Protection rating IP 44
	Protection rating IP 54
	Protection rating IP 55
	Protection rating IP 65
	Protection rating IP 66
	Protection rating IP 67
	Protection rating IP 68

Metals

	Aluminium
	Aluminium/steel
	Stainless steel, rustproof
	Stainless steel, rustproof
	Stainless steel, rustproof
	Copper
	Brass
	Steel
	Malleable iron
	Die-cast zinc

Plastics

	Acrylonitrile butadiene styrene
	Duroplast, Aminoplast, type 131.5
	Duroplast, melamine resin, type 150
	Ethylene vinyl acetate



Plastics


FA	Fibre-proof material DIN 28091
GFK	Fibre-glass-reinforced plastic
NBR SBR	Rubber mixture
NBR	Nitrile rubber
PETR	Petrolatum
PA	Polyamide
PA/ GF	Polyamide, fibre-glass reinforced
PBPT	Polybutylene terephthalate
PC	Polycarbonate
PE	Polyethylene
PP	Polypropylene
PP/GF	Polypropylene, fibre-glass reinforced
PS	Polystyrene
PVC	Polyvinylchloride
ZELL PE	Cellular polyethylene



Numeric directory



GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page	GTIN	Item no.	Page
6190386	/100 pc. 5012010	216	6515400	5092431	74	5541158	5096849	27	5708902	5099611	207
			6515431	5092433	75	5051466	5096852	28	5708933	5099708	208
			6426690	5092441	81	5541394	5096865	29			
6427628	5015265	237	5080886	5092451	80	5362029	5096874	70	6517381	5240030	232
6427680	5015270	237	5247098	5092460	83	5362036	5096875	69	6521180	5240031	233
			5613596	5092472	82	5077077	5096877	30	6521159	5240102	233
6672813	5057630	238	5952817	5092701	92	5077091	5096879	32	6521166	5240104	233
6672820	5057640	238	5035053	5092800	87	5531135	5096884	216	6521173	5240106	233
6672837	5057645	238	5035114	5092808	89	5531197	5096886	216	6524181	5240360	234
6672844	5057690	238	5047223	5092812	90	6776368	5096900	218	6524242	5240362	234
			5035176	5092816	86	6585588	5096950	13	6524259	5240366	234
6741908	5080301	132	5035237	5092824	88	6585595	5096953	14	6524273	5240370	234
6741915	5080303	132	5047254	5092828	91	6585564	5096961	15	6524297	5240374	234
6741922	5080305	132				6585571	5096963	16	6524433	5240380	234
6741939	5080307	132	5390671	5093015	160	6608805	5096971	17	6524457	5240382	234
6741946	5080309	133	5390732	5093023	159	6608812	5096973	18	6524464	5240386	234
6741953	5080311	133	5030881	5093171	168				6524471	5240390	234
6741960	5080313	133	5390978	5093236	162	5990116	5096974	47	6524488	5240394	234
6741977	5080315	133	5391036	5093252	161	6608782	5096975	19			
			5391098	5093260	163						
6676965	5081070	155	5087250	5093270	167	5995012	5096976	48	5888123	price/100 5407995	240
6676972	5081072	156	5022619	5093272	170	6608799	5096977	20	5888154	5407997	240
			5022732	5093275	169						
6034352	5081690	135	5867050	5093277	171	6487325	5096981	25	5674573	5408002	241
6087723	5081694	137	5076551	5093380	64	6608768	5096982	21	5674627	5408004	241
6427444	5081698	136	6098583	5093382	66	6608775	5096983	22	5854265	5408006	241
5614364	5081800	148	5299448	5093391	65	6608744	5096985	23			
6532766	5081802	149	6412952	5093500	35						
6532773	5081804	150	6412969	5093502	37	6487332	5096987	26			
6415656	5081975	140	6159598	5093508	215	6608751	5096988	24	6117611	/pc. 6117465	85
6415663	5081977	139	6159604	5093511	40				6117673	6117473	84
			6159628	5093513	44	5995029	5096990	217			
5685333	5082382	154	6159642	5093516	41	5995036	5096992	217			
6415717	5082430	151	6159659	5093518	45	5995043	5096994	217			
6415724	5082432	152	6159666	5093522	36						
6415731	5082434	153	6159680	5093524	39	5708896	5097065	206			
			6159697	5093526	42	5478683	5097447	179			
5022978	5083400	172	6159703	5093531	38	5709121	5097448	180			
			6159710	5093533	43	5578116	5097453	107			
5525134	5084008	143	6423217	5093594	67	5736561	5097454	113			
5525196	5084012	143	6423224	5093596	68	5578123	5097607	108			
5525257	5084016	144	5478546	5093623	181	5578130	5097615	109			
5525318	5084020	142	5709022	5093625	182	5578147	5097623	110			
5525370	5084024	142	5708841	5093726	205	5578154	5097631	111			
5525493	5084032	145	5962243	5093988	165	5578161	5097650	112			
5525554	5084036	145	5805991	5093996	164	5578185	5097820	114			
5525615	5084040	144	6463831	5093998	166	5812258	5097822	115			
5110750	5084048	146				5578215	5097858	116			
			6603695	5094210	183	5578260	5097939	117			
6816095	5088554	203	6603701	5094212	184	5578277	5097976	97			
6816088	5088556	204	6603718	5094230	177						
			6603725	5094232	178	5683339	5098380	227			
6440573	5088564	200	6603732	5094240	175	5683346	5098382	228			
6440580	5088565	201	6603749	5094242	176	5683384	5098390	229			
6190263	5088566	191	5648482	5094574	186	5683391	5098392	230			
6329854	5088568	192	5709084	5094576	188	5406839	5098404	119			
6037421	5088573	195	5708872	5094605	187	5406846	5098407	120			
6037476	5088579	193	5478621	5094608	185	5406853	5098411	121			
6037490	5088585	194				5848516	5098412	223			
6423170	5088591	189	6159802	5095161	50	5625124	5098413	128			
6423187	5088593	190	6159819	5095162	54	5787372	5098415	129			
5872658	5088629	202	6159826	5095163	58	5773610	5098419	130			
5981176	5088635	199	6159833	5095164	62	5406860	5098422	122			
6422654	5088640	196	6161140	5095251	52	5787389	5098425	131			
5780717	5088651	197	6161324	5095252	56	5406877	5098427	123			
6148561	5088654	198	6161331	5095253	60	5406884	5098431	124			
			6162000	5095281	51	5848523	5098432	224			
5237341	5089650	216	6162185	5095282	55	5406891	5098442	125			
5709350	5089660	216	6162338	5095283	59	5406907	5098446	126			
5709367	5089662	216	6162819	5095284	63	5406914	5098450	127			
			6163014	5095331	53	5848530	5098452	225			
			6163243	5095332	57	5410461	5098470	218			
5461111	price/pac 5091322	212	6163427	5095333	61	5813521	5098475	217			
5461296	5091438	212	6163557	5095364	215	5578307	5098514	98			
5461470	5091527	213	6423194	5095381	71	5578314	5098522	99			
			6423200	5095383	72	5578338	5098557	100			
5461654	5091683	212	6337620	5095609	214	5578345	5098571	95			
6465644	5091722	211				5578352	5098575	96			
			5425182	5096786	211	5578369	5098600	101			
6426713	5092420	77	5921738	5096812	211	5578376	5098603	102			
6426720	5092422	76	5544517	5096822	214	5578383	5098611	103			
6426751	5092424	79	5288282	5096835	31	5578390	5098630	104			
6426768	5092426	78	5288299	5096836	33	5578413	5098646	105			



OBO Bettermann Holding GmbH Co. KG

P.O. Box 1120
58694 Menden, Germany

Customer Service

Tel.: +49 23 73 89 - 17 00
Fax: +49 23 73 89 - 12 38
export@obo.de

www.obo-bettermann.com

Building Connections

